













By Demes weekly super deals are here
CCTV









Analog Cameras HD/CVBS - Mini-Dome









Reference	Model	Photo	Description
<u>SAM-4552</u>	SAM-4552		4 in 1 AirSpace dome PRO series with IR of 20 m for indoors. 1/2,9" CMOS, 2MP. 4 in 1 output (HDCVI / HDTV / AHD / 960H) via switch. ICR filter. 2,8 mm lens. OSD, AWB, AGC, BLC, digital WDR, 3D-NR. 12V DC.
<u>SAM-4554</u>	SAM-4554		4 in 1 AirSpace dome PRO series with IR of 20 m for outdoors. 1/2,9" CMOS, 2MP . 4 in 1 output (HDCVI / HDTV / AHD / 960H) from switch. ICR filter. 2.8 mm lens. OSD, AWB, AGC, BLC, WDR digital, 3D -NR. IP66. 12V DC.
<u>SAM-4549</u>	SAM-4549		4 in 1 AirSpace dome PRO series with IR of 20 m for outdoors. 1/2,9" CMOS, 2MP. 4 in 1 output (HDCVI / HDTV / AHD / 960H) via switch. ICR filter. 2,8 mm lens. OSD, AWB, AGC, BLC, WDR digital, 3D-NR. IP66. 12V DC.
<u>HYU-700</u>	HYU-700		4 in 1 dome PRO series with IR illumination of 15~20 m for outdoors. 1/2,9" CMOS, 2MP at 1080P. 4 in 1 video output switch via DIP switch. 2,8 mm lens. ICR filter. OSD, AWB, AGC, 2D-DNR, BLC, digital WDR. IP65. Lightning-proof. 3AXIS. 12V DC.
<u>SAM-4564</u>	SAM-4564		4 in 1 AirSpace dome PRO series with IR of 20 m for indoors. 1/2,9" Sony CMOS, 2MP. 4 in 1 output (HDCVI / HDTV / AHD / 960H) switch. ICR filter 2.8 mm lens. OSD, AWB, AGC, BLC, digital WDR, 3D-NR. 12V DC
<u>SAM-2976N</u>	SAM-2976N		4 in 1 fixed dome LITE series with IR illumination of 20 meters, for outdoors. 1/3" CMOS, 1.3MP @ 720p. 4 in 1 output (HDCVI/HDTV/AHD/960H). 2.8 mm fixed lens (90°). ICR. AWB, AGC, AES. IP66. 3AXIS. 12V DC.
<u>SAM-4577</u>	SAM-4577		4 in 1 AirSpace dome PRO series with IR of 20 m, for indoors. 1/2,5" Sony CMOS, 5MP. 4-in-1 output (HDCVI / HDTV / AHD / 960H) switch. ICR filter 2.8 mm lens. OSD, AWB, AGC, 2D / 3D-DNR, digital WDR. 12V DC









<u>HYU-503</u>	HYU-503		4 in 1 dome PRO series with Smart IR of 20 m for outdoors. 2MP CMOS. 4 in 1 (HDCVI / HDTVI / AHD / 960H). 2,8 mm fixed lens (103°). ICR filter. OSD, digital WDR. IP66. 3AXIS. 12V DC.
<u>SAM-4565</u>	SAM-4565		4 in 1 AirSpace dome PRO series with IR of 20 m, for outdoors. 1/2.9" Sony CMOS, 2MP. 4 in 1 output (HDCVI / HDTVI / AHD / 960H) switch. ICR filter 2.8 mm lens. OSD, AWB, AGC, BLC, digital WDR, 3D-NR. IP67 3AXIS. 12V DC
<u>SAM-4569</u>	SAM-4569		4 in 1 AirSpace dome PRO series with IR of 20 m for outdoors. 1/2.9" Sony CMOS, 2MP. 4-in-1 output (HDCVI / HDTVI / AHD / 960H) switch. ICR filter 2.8 mm lens. OSD, AWB, AGC, BLC, digital WDR, 3D-NR. IP67 12V DC
<u>SAM-4570</u>	SAM-4570		4 in 1 AirSpace dome PRO series with IR of 20 m for outdoors. 1/2.9" Sony CMOS, 2MP. 4 in 1 output (HDCVI / HDTVI / AHD / 960H) switch. ICR filter. 2,8 mm lens. OSD, AWB, AGC, BLC, WDR digital, 3D-NR. IP67. 12V DC.
<u>SAM-4318N</u>	SAM-4318N		4 in 1 LITE dome series with Smart IR of 20 m for outdoors. 1/2.7" CMOS, 2MP. 4 in 1 output (HDCVI / HDTVI / AHD / 960H). ICR. 2,8 mm fixed lens. OSD, AWB, MWB, AGC, BLC, real WDR, 2D-DNR. IP66. 3AXIS. 12V DC.
<u>SAM-4562</u>	SAM-4562		4 in 1 AirSpace dome PRO series with IR of 20 m for outdoors. 1/2.9" Sony CMOS at 2MP. 4 in 1 output (HDCVI / HDTVI / AHD / 960H) via switch. ICR filter. 2,8 mm lens. OSD, AWB, AGC, BLC, WDR digital, 3D-NR. IP67. 3AXIS. 12V DC.
<u>SAM-4575</u>	SAM-4575		4 in 1 AirSpace dome PRO series with IR of 20 m for outdoors. 1 / 2.5 "Sony CMOS, 5MP. 4 in 1 output (HDCVI / HDTVI / AHD / 960H) switch. ICR filter 2.8 mm lens. OSD, AWB, AGC, 2D / 3D-DNR, digital WDR. IP66 3AXIS. 12V DC
<u>HYU-808</u>	HYU-808		





<u>HYU-704</u>	HYU-704		4 in 1 dome PRO series with IR illumination of 20~30 m for outdoors. 1/2,9" CMOS, 2MP at 1080P. 4 in 1 video output via DIP switch. 2,8 mm lens. ICR filter. OSD, AWB, AGC, 2D-DNR, BLC, digital WDR. IP65. Lightning-proof. 3AXIS. 12V DC.
<u>HYU-765</u>	HYU-765		4-in-1 HYUNDAI NEXT GEN dome PRO series with 40 m Smart IR for outdoors. 2MP CMOS. 1080P @ 25/30fps. 4-in-1 video output switch. 2.8 mm lens (106.4 °). ICR filter AWB, AGC, BLC, HLC, BLC, digital WDR, 3D-DNR. . IP67 3AXIS. 12V DC
<u>SAM-3437N</u>	SAM-3437N		4 in 1 dome LITE series with IR illumination of 30 m for outdoors. 1/2,7" CMOS, 2MP at 1080P. 4 in 1 output (HDCVI / HDTVI / AHD / 960H). ICR filter. 3,6 mm lens. OSD, AWB, AGC, 2D/3D-NR, digital WDR. IP66. 3AXIS. 12V DC.
<u>SAM-4033</u>	SAM-4033		4 in 1 extraflat dome PRO series with IR 2x array of 20 m, for outdoors. 1/3" Sony CMOS, 2MP at 1080P. 4 in 1 output by DIP switch (HDCVI / HDTVI / AHD / CVBS 960H). 3,6 mm fixed lens. ICR filter. OSD, AWB, AGC, BLC, for indoors. 12V DC
<u>SAM-4327N</u>	SAM-4327N		4 in 1 dome PRO series with IR of 30 m for outdoors. 1/2,9" Sony CMOS, 2 MP. 4 in 1 output (HDCVI / HDTVI / AHD / 960H). ICR filter. 2,8 mm lens. OSD, AWB, AGC, DNR, digital WDR. IP66. 3AXIS. 12V DC.
<u>SAM-4550</u>	SAM-4550		4 in 1 AirSpace dome PRO series with IR of 30 m for outdoors. 1/2,9" CMOS, 2MP. 4 in 1 output (HDCVI / HDTVI / AHD / 960H) via switch. ICR filter. 2,7 ~ 13,5 mm varifocal lens. OSD, AWB, AGC, BLC, digital WDR, 3D-NR. IP66. 12V DC.
<u>SAM-4555</u>	SAM-4555		4 in 1 AirSpace dome PRO series with IR of 30 m for outdoors. 1/2,9" CMOS, 2 MP. 4 in 1 output (HDCVI / HDTVI / AHD / 960H) switch. ICR filter. 2.7 ~ 13.5 mm varifocal lens. OSD, AWB, AGC, BLC, Digital WDR, 3D-NR, IP66, 12V DC.
<u>SAM-4556</u>	SAM-4556		4 in 1 AirSpace dome PRO series with IR of 30 m for outdoors. 1/2,9" CMOS, 2MP. 4 in 1 output (HDCVI / HDTVI / AHD / 960H) switch. ICR filter. 2.7 ~ 13.5 mm varifocal lens. OSD, AWB, AGC, BLC, Digital WDR, 3D-NR, IP66, 12V DC.

<u>SAM-4566</u>	SAM-4566		4 in 1 AirSpace dome PRO series with IR of 30 m for outdoors. 1/2,9" Sony CMOS, 2MP. 4-in-1 output (HDCVI / HDTVI / AHD / 960H) switch. ICR filter. 2.7 ~ 13.5 mm varifocal lens. OSD, AWB, AGC, BLC, digital WDR, 3D-NR. IP67 3AXIS. 12V DC
<u>SAM-4567</u>	SAM-4567		4 in 1 AirSpace dome PRO series with IR of 30 m for outdoors. 1/2,9" Sony CMOS, 2MP. 4-in-1 output (HDCVI / HDTVI / AHD / 960H) switch. ICR filter 2.7 ~ 13.5 mm varifocal lens. OSD, AWB, AGC, BLC, digital WDR, 3D-NR. IP67 12V DC
<u>SAM-4568</u>	SAM-4568		4 in 1 AirSpace dome PRO series with IR of 30 m, for outdoors. 1/2,9" Sony CMOS, 2MP. 4-in-1 output (HDCVI / HDTVI / AHD / 960H) switch. ICR filter 2.7 ~ 13.5 mm varifocal lens. OSD, AWB, AGC, BLC, digital WDR, 3D-NR. IP67 12V DC
<u>HYU-703</u>	HYU-703		4 in 1 dome PRO series with IR illumination of 20~30 m for outdoors. 1/2,9" CMOS, 2MP at 1080P. 4 in 1 video output via DIP switch. 2,8 ~ 12 mm varifocal lens. ICR filter. OSD, AWB, AGC, 2D-DNR, BLC, digital WDR. IP65. Lightning-proof. 3AXIS. 12V DC.
<u>SAM-4590</u>	SAM-4590		4 in 1 AirSpace dome StarLight Full Color ULTRAPRO series with white illumination 15 m for outdoors. 1/2,8" Sony STARVIS CMOS, 2MP. 4 in 1 output (HDCVI / HDTVI / AHD / 960H) via switch. ICR filter. 2,8 mm lens. OSD, AWB, AGC, 2D/3D-DNR, WDR 120dB. IP67. 12V DC.
<u>HYU-512</u>	HYU-512		4 in 1 fixed dome PRO series with Smart IR of 40 m for outdoors. 2MP CMOS. 4 in 1 output (HDCVI / HDTVI / AHD / 960H). 2,8 ~ 12 mm varifocal lens (102,25°~32°). ICR. OSD, ATW/MWB, AGC, BLC, Digital WDR. IP66. 3AXIS. 12V DC.
<u>SAM-4563</u>	SAM-4563		4 in 1 AirSpace dome PRO series with IR of 30 m for outdoors. 1/2,9" Sony CMOS at 2MP. 4 in 1 output (HDCVI / HDTVI / AHD / 960H) via switch. ICR filter. 2,7 ~ 13,5 mm varifocal lens. OSD, AWB, AGC, BLC, WDR digital, 3D-NR. IP67. 3AXIS. 12V DC.
<u>SAM-4561</u>	SAM-4561		4 in 1 AirSpace dome PRO series with IR of 15 m for outdoors. 1/2,9" Sony CMOS, 2MP. 4 in 1 output (HDCVI / HDTVI / AHD / 960H) from switch. ICR filter. 2,8 mm fixed lens. OSD, AWB, AGC, BLC, WDR digital, 3D-NR. IP66. 12V DC.


<u>SAM-4321N</u>	SAM-4321N		4 in 1 dome LITE series with Smart IR of 30 m for outdoors. 1/2,7" CMOS, 2MP. 4 in 1 output (HDCVI / HDTVI / AHD / 960H). ICR filter. 2,8 ~ 12 mm varifocal lens. OSD, AWB, MWB, AGC, BLC, real WDR, 2D-DNR. IP66. 3AXIS. 12V DC.
<u>SAM-4591</u>	SAM-4591		4 in 1 AirSpace dome StarLight Full Color ULTRAPRO series with white illumination of 15 m, for outdoors. 1/2,8" Sony STARVIS CMOS, 2MP. 4 in 1 output (HDCVI / HDTVI / AHD / 960H) from switch. ICR filter. 2,8 mm lens. OSD, AWB, AGC, 2D/3D-DNR, WDR 120dB. IP67. 12V DC.
<u>SAM-3445</u>	SAM-3445		4 in 1 fixed dome ULTRAPRO series with IR illumination of 30 m, for outdoors. 1/2,9" Sony Exmor CMOS, 2MP @ 1080p. 4 in 1 output (HDCVI / HDTVI / AHD / 960H). ICR filter. 3.6 mm fixed lens. OSD, AWB, AGC, 2D/3D-NR, HLC, real WDR 120dB, defog, Sense Up 32X, motion detection and privacy mask. IP66. 3AXIS. DC 12V.
<u>HYU-506</u>	HYU-506		4 in 1 dome PRO series with Smart IR of 20 m for outdoors. CMOS, 2MP. 4 in 1 (HDCVI / HDTVI / AHD / 960H). 2,8 mm fixed lens (103°). ICR filter. OSD, digital WDR. IP66. 3AXIS. 12V DC.
<u>HYU-507</u>	HYU-507		HDTVI dome PRO series with Smart IR of 40 m for outdoors. 3MP CMOS. HD-TVI video output. 2,8 mm (84°) fixed lens. ICR filter. OSD, ATW/MWB, AGC, BLC, digital WDR. IP66. 3AXIS. 12V DC.
<u>HYU-566</u>	HYU-566		HD-TVI dome PIR series with Smart IR of 20 m and motion detection by active PIR, for outdoors. 2MP CMOS. HD-TVI video output. 2,8 mm lens (103°). 0,01 lux color. ICR. OSD, ATW, AGC, BLC, DNR, mirror and image adjustment. Visual alarm via white led. IP67. 3AXIS. 12V DC.
<u>HYU-809</u>	HYU-809		4 in 1 HYUNDAI NEXT GEN dome PRO series with Smart IR of 30 m for outdoors. 2MP CMOS. 1080P resolution @ 25/30fps 4-in-1 video output switch. 2.8 mm lens (106.4 °). ICR filter AWB, AGC, BLC, HLC, digital WDR, 2D-DNR. It incorporates microphone. Supports coaxial audio. IP67 3AXIS. 12V DC
<u>SAM-4574</u>	SAM-4574		4 in 1 AirSpace dome PRO series with IR of 15 m for outdoors. 1/2,5" Sony CMOS at 5MP. 4 in 1 output (HDCVI / HDTVI / AHD / 960H) from switch. ICR filter. 2,7 ~ 13,5 mm varifocal lens. OSD, AWB, AGC, 2D/3D-DNR, WDR digital. IP66. 12V DC.









<u>SAM-4576</u>	SAM-4576		4 in 1 AirSpace dome PRO series with IR of 30 m for outdoors. 1/2,5" Sony CMOS, 5MP. 4 in 1 output (HDCVI / HDTVI / AHD / 960H) switch. ICR filter 2.8 ~ 12 mm varifocal lens. OSD, AWB, AGC, 2D / 3D-DNR, digital WDR. IP66 3AXIS. 12V DC
<u>HYU-389</u>	HYU-389		HD-TVI fixed dome PRO series with Smart IR of 20 m for outdoors. 2MP CMOS. HD-TVI video output. 2,8 mm fixed lens (103°). ICR filter. ATW, AGC, DNR. IP66. 3AXIS. 12V DC. PoC compatible
<u>SAM-4585</u>	SAM-4585		4 in 1 AirSpace dome LITE series with IR of 25 m for indoors. 1/2,7" CMOS, 8MP. 4 in 1 output (HDCVI / HDTVI / AHD / 960H) switch. ICR filter. 2,8 mm lens. OSD, AWB, AGC, BLC, 3D-DNR, privacy mask. 12V DC.
<u>SAM-4500</u>	SAM-4500		4 in 1 dome PRO series with IR of 30 m for outdoors. 1/2,8" CMOS, 5MP. 4 in 1 output (HDCVI / HDTVI / AHD / 960H) switch OSD. ICR filter. 3,6 mm lens. OSD, AWB, AGC, 2D/3D-DNR, WDR true, Defog, motion detection and privacy mask. IP66. 3AXIS. 12V DC.
<u>SAM-4224</u>	SAM-4224		4 in 1 fixed dome, PRO series with IR illumination of 30 m, for outdoors. 1/2,7" CMOS, 5MP. 4 in 1 output (HDCVI @ 4MP, HDTVI @ 5MP/4MP, AHD @ 5MP/4MP, CVBS @ 960H). 3,6 mm fixed lens. AWB, AGC, AES, 2D-NR. IP66. 3AXIS. 12V DC.
<u>HYU-482</u>	HYU-482		HD-TVI fixed dome PIR series with Smart IR of 20 m and motion detection by active PIR, for outdoors. 2MP CMOS. HD-TVI video output. 2,8 mm fixed lens (103,5°). 0,005 lux. ICR filter. OSD, ATW, MWB, AGC, BLC, real WDR 120dB, 3D-DNR, mirror, motion detection and privacy mask. Visual alarm by white led. IP67. 3AXIS. 12V DC.
<u>HYU-516</u>	HYU-516		4 in 1 dome PRO series with Smart IR of 40 m for outdoors. 2MP CMOS. 4 in 1 output (HDCVI / HDTVI / AHD / 960H). 2,8 ~ 12 mm varifocal lens (102,25°~32°). ICR filter. OSD, ATW/MWB, AGC, BLC, digital WDR. IP66. 3AXIS. 12V DC.
<u>SAM-4329</u>	SAM-4329		4 in 1 dome PRO series with Smart IR of 30 m for outdoors. 1/2,9" Sony CMOS, 2MP. 4 in 1 output (HDCVI / HDTVI / AHD / 960H). ICR. 2,8 ~ 12 mm varifocal lens. OSD, AWB, MWB, AGC, BLC, real WDR, 2D-DNR. IP66. 3AXIS. 12V DC.

<u>SAM-4586</u>	SAM-4586		4 in 1 AirSpace dome LITE series with IR of 20 m for outdoors. 1/2.7" CMOS, 8MP. 4-in-1 output (HDCVI / HDTVI / AHD / 960H) switch. ICR filter 2.8 mm lens. OSD, AWB, AGC, BLC, 3D-DNR, privacy mask. IP67 12V DC.
<u>SAM-4583</u>	SAM-4583		4 in 1 AirSpace dome LITE series with IR of 20 m for outdoors. 1/2.7" CMOS, 8MP. 4-in-1 output (HDCVI / HDTVI / AHD / 960H) switch. ICR filter 2.8 mm lens. OSD, AWB, AGC, BLC, 3D-DNR, privacy mask. IP67 12V DC
<u>HYU-246</u>	HYU-246		4 in 1 PRO series with IR illumination of 30 meters, for outdoors. 1/3" CMOS, 3 MP. 4 in 1 output via DIP switch (HDCVI @1080P / HDTVI @3MP / AHD @3MP / CVBS @960H). ICR filter. 2.7~13 mm varifocal lens. OSD, AWB, MWB, AGC, AES, 2D-DNR, BLC, digital WDR. IP66. 12V DC
<u>SAM-1521A</u>	SAM-1521A		AirSpace® StarLight Next Generation anti-vandal outdoor fixed Day/Night dome (mechanical filter). 1/3" Sony® Super HAD II CCD 1000 lines. 0.00001 lux. 2.8 ~ 12mm Auto Iris lens. 32X Digital Zoom. OSD, Sense Up, BLC, HSBLIC, Digital WDR, 3D-DNR, motion detection and privacy mask. IP66. 12V.
<u>HYU-814</u>	HYU-814		
<u>HYU-576</u>	HYU-576		4 in 1 dome PRO series with Smart IR of 20 m for outdoors. 5MP CMOS. 4 in 1 (HDCVI / HDTVI / AHD / 960H). 2,8 mm (85,5°) fixed lens. ICR. OSD, ATW, MWB, AGC, BLC, digital WDR, 2D-DNR, brightness, sharpness, mirror. IP67. 3AXIS. 12V DC.
<u>HYU-813</u>	HYU-813		
<u>HYU-777</u>	HYU-777		4-in-1 HYUNDAI NEXT GEN dome PRO series with Smart IR of 20 m for outdoors. 2MP CMOS. 1080P @ 25/30fps 4 in 1 video output switch. 2.8 mm (106 °) lens. ICR filter AWB, AGC, BLC, HLC, digital WDR, 2D-DNR. It incorporates PIR detector, strobe and siren. IP67 3AXIS. 12V DC

<u>SAM-4250</u>	SAM-4250		4 in 1 dome PRO series with IR of 40 m, for outdoors. 1/2,7" CMOS @ 1080P. 4 in 1 output (HDCVI / HDTVI / AHD / 960H) by switch. ICR filter. 2,7 ~ 13,5 mm motorized lens. OSD, AWB, AGC, AES, 2D/3D-DNR, digital WDR, motion detection and privacy mask. IP66. 3AXIS. 12V DC.
<u>HYU-695</u>	HYU-695		4 in 1 dome StarLight series with IR illumination of 20~30 m for outdoors. 1/2,8" Sony CMOS, 2MP at 1080P. 4 in 1 video output switch. 2,8~12 mm motor lens with autofocus. ICR filter. OSD, AWB, AGC, 2D/3D-DNR, BLC, digital WDR, sense up, defog, mirror, motion detection and privacy mask. IP66. Lightning-proof. 3AXIS. 12V DC.
<u>HYU-696</u>	HYU-696		4 in 1 dome StarLight series with IR illumination of 20~30 m for outdoors. 1/2,8" Sony CMOS, 2MP at 1080P. 4 in 1 video output switch. 2,8~12 mm motor lens with autofocus. ICR filter. OSD, AWB, AGC, 2D/3D-DNR, BLC, digital WDR, sense up, defog, mirror, motion detection and privacy mask. IP66. Lightning-proof. 3AXIS. 12V DC.
<u>SAM-4334</u>	SAM-4334		4 in 1 dome PRO series with IR illumination of 40 m for outdoors. 1/2,9" Sony CMOS, 2 MP. 4 in 1 output (HDCVI / HDTVI / AHD / 960H). ICR filter. 2,7~13,5 mm motorized lens. OSD, AWB, AGC, DNR, digital WDR. IP66. 3AXIS. 12V DC.
<u>HYU-570</u>	HYU-570		HD-TVI dome PRO series with Smart IR of 20 m for outdoors. 5MP CMOS. HD-TVI video output. 2,8 mm lens (85,5°). ICR. OSD, ATW, MWB, AGC, BLC, digital WDR, 2D-DNR, image adjustment. IP67. 3AXIS. 12V DC. Compatible with PoC.af.
<u>HYU-57N</u>	HYU-57N		4 in 1 dome StarLight series for outdoors. 1/2,8" Sony CMOS, 2,1MP at 1080P. 4 in 1 output (HDCVI / HDTVI / AHD / 960H). 2,7~13,5 mm StarLight varifocal lens. OSD, AWB, ATW, AGC, BLC, digital WDR, 2D/3D-DNR, defog, mirror, motion detection and privacy mask. IP65, Lightning-proof. 3AXIS. 12V DC.
<u>SAM-4502</u>	SAM-4502		4 in 1 dome PRO series with IR of 40 m for outdoors. 1/2,8" CMOS, 5MP. 4 in 1 output (HDCVI / HDTVI / AHD / 960H) from switch OSD. ICR filter. 2,8 ~ 13,5 mm varifocal lens. OSD, AWB, AGC, 2D/3D-DNR, Real WDR, Defog, motion detection and privacy mask. IP66. 3AXIS. 12V DC.
<u>SAM-3448</u>	SAM-3448		4 in 1 fixed dome ULTRAPRO series with IR illumination of 40 m , for outdoors. 1/2.9" Sony Exmor CMOS, 2MP @ 1080p. 4 in 1 output (HDCVI/HDTVI/AHD/960H). ICR filter. 2.8~12 mm varifocal lens. OSD, AWB, AGC, HLC, real WDR 120dB, defog, Sense Upp 32X, motion detection and privacy mask. IP66. 3AXIS. DC 12V.


<u>HYU-509</u>	HYU-509		HDTVI dome StarLight with Smart IR of 40 m for outdoors. 2MP CMOS. HDTVI video output. 2,8 ~ 12 mm (103°~32,1°) motor lens with autofocus. ICR filter. OSD, ATW/MWB, AGC, BLC, HLC, real WDR 120dB, 3D-DNR, mirror mode, sharpness and brightness adjustment, motion detection and privacy mask. IP67. 3AXIS. 12V DC
<u>SAM-4349N</u>	SAM-4349N		4 in 1 dome PRO series with Smart IR of 40 m for outdoors. 1/2,7" CMOS, 5MP. 4 in 1 output (HDCVI / HDTVI / AHD / 960H). ICR filter. 2,7 ~ 13,5 mm varifocal lens. OSD, AWB, MWB, AGC, BLC, digital WDR, 2D-NR. IP66. 3AXIS. 12V DC.
<u>SAM-4354N</u>	SAM-4354N		4 in 1 dome PRO series with Smart IR of 40 m for outdoors. 1/2,7" CMOS, 5MP. 4 in 1 output (HDCVI / HDTVI / AHD / 960H). ICR filter. 2,7 ~ 13,5 mm motorized lens. OSD, AWB, MWB, AGC, BLC, digital WDR, 2D-NR. IP66. 3AXIS. 12V DC.
<u>HYU-672</u>	HYU-672		NightFighter 4 in 1 dome with STARLIGHT technology and Smart IR of 70 m for outdoors. 2MP CMOS. 4 in 1 switch video output. 2,7 ~ 13,5 mm motor lens (102°~31°). ICR filter. OSD, AWB, AGC, BLC, HLC, WDR 120dB, 3D-DNR, image adjustment. IP67. 3AXIS. 12V DC.
<u>SAM-4582</u>	SAM-4582		4 in 1 AirSpace dome LITE series with IR of 15 m for outdoors. 1/2,7" CMOS, 8MP. 4-in-1 output (HDCVI / HDTVI / AHD / 960H) switch. ICR filter 2.7 ~ 13.5 mm varifocal lens. OSD, AWB, AGC, BLC, 3D-DNR, privacy mask. IP67 12V DC
<u>SAM-4584</u>	SAM-4584		4 in 1 AirSpace dome LITE series with IR of 30 m for outdoors. 1/2,7" CMOS, 8MP. 4 in 1 output (HDCVI / HDTVI / AHD / 960H) switch. ICR filter. 2,7 ~ 13,5 mm varifocal lens. OSD, AWB, AGC, BLC, 3D-DNR, privacy mask. IP67. 12V DC.
<u>SAM-4227</u>	SAM-4227		4 in 1 fixed dome PRO series with IR of 40 m for outdoors. 1/2,7" CMOS, 5MP. 4 in 1 output (HDCVI @ 4MP, HDTVI @ 5MP/4MP, AHD @ 5MP/4MP, CVBS @ 960H). 2,8 ~ 13,5 mm varifocal lens. AWB, AGC, AES, 2D-NR. IP66. 3AXIS. 12V DC.
<u>SAM-4587</u>	SAM-4587		4 in 1 AirSpace dome LITE series with IR of 30 m for outdoors. 1/2,7" CMOS, 8MP. 4 in 1 output (HDCVI / HDTVI / AHD / 960H) switch. ICR filter. 2,7 ~ 13,5 mm varifocal lens. OSD, AWB, AGC, BLC, 3D-DNR, privacy mask. IP67. 12V DC.









<u>HYU-759</u>	HYU-759		NightFighter 4 in 1 dome with STARLIGHT technology and Smart IR of 70 m for outdoors. 2MP CMOS. 4 in 1 switch video output. 2,7 ~ 13,5 mm motor lens (102°~31°). ICR filter. OSD, AWB, AGC, BLC, HLC, WDR 120dB, 3D-DNR, image adjustment. IP67. 3AXIS. 12V DC.
<u>HYU-390</u>	HYU-390		HD-TVI fixed dome PRO series with Smart IR of 40 m for outdoors. 2MP CMOS. HD-TVI video output. 2,7 ~ 12 mm varifocal lens (102,25°~32°). ICR. ATW, AGC, DNR. IP66. 3AXIS. 12V DC. PoC compatible .
<u>HYU-547</u>	HYU-547		HD-TVI StarLight with Smart IR of 20 m, for indoors. 2MP CMOS. HDTV video output. 2,8 ~ 12 mm motorized lens (103°~32,1°). ICR filter. OSD, ATW, AGC, BLC, WDR 120 dB, 3D-DNR, brightness, sharpness, mirror, motion detection and privacy mask. IP50. 3AXIS. 12V DC.
<u>HYU-548</u>	HYU-548		HDTV dome Starlight with Smart IR of 40 m for outdoors. 2MP CMOS. HDTV output. 2,8 ~ 12 mm (103°~32,1°) motorized lens with autofocus. ICR. OSD, ATW/MWB, AGC, BLC, HLC, real WDR 120dB, 3D-DNR, mirror mode, brightness and sharpness adjustment, motion detection and privacy mask. IP67. 3AXIS. 12V DC.
<u>HYU-586</u>	HYU-586		4 in 1 dome Color View series with white illumination of 20 m for outdoors. 2MP CMOS. 4 in 1 output (HDCVI / HDTV / AHD / 960H). 3,6 mm lens (83,6°). 24 hour color mode (no switch to B/W). OSD, ATW/MWB, AGC, BLC, real WDR 120dB, 3D-DNR, image adjustment, mirror mode, motion detection and privacy mask. IP67. 3AXIS. 12V DC.
<u>HYU-589</u>	HYU-589		4 in 1 dome PRO series with Smart IR of 30 m for outdoor. CMOS of 8,3MP. 4 in 1 output (HDCVI / HDTV / AHD / 960H). 2,8 mm lens (102,2°). ICR filter. OSD, ATW, MWB, AGC, BLC, digital WDR, DNR, brightness, sharpness, mirror. IP67. 3AXIS. 12V DC.
<u>HYU-604</u>	HYU-604		4 in 1 vandal dome PRO series with Smart IR of 60 m for outdoors. 2MP CMOS. 4 in 1 output (HDCVI / HDTV / AHD / 960H). 2,7~13,5 mm motorized varifocal lens (103°~32,1°). AGC, AWB, motion detection and privacy mask. Real WDR 120 dB , 3D-DNR, brightness, sharpness, mirror. IP67. IK10 3AXIS. 12V DC.
<u>HYU-573</u>	HYU-573		HDTV dome Starlight with Smart IR of 40 m, for outdoors. 2MP CMOS. HDTV output. 2,8~12 mm (103°~32,1°) motorized lens with autofocus. ICR. OSD, ATW/MWB, AGC, BLC, HLC, real WDR 120dB, 3D-DNR, mirror mode, brightness and sharpness adjustment, motion detection and privacy mask. IP67. 3AXIS. 12V DC.

<u>HYU-577</u>	HYU-577		4 in 1 dome PRO series with Smart IR of 40 m for outdoors. 5MP CMOS. 4 in 1 output (HDCVI / HDTV / AHD / 960H). 2,7 ~ 13,5 mm motorized lens (95,7°~29,1°). ICR filter. OSD, ATW, MWB, AGC, BLC, digital WDR, 2D-DNR, brightness, sharpness, mirror. IP67. 3AXIS. 12V DC.
<u>HYU-588</u>	HYU-588		4 in 1 dome PRO series with Smart IR of 30 m, vandal proof for outdoors. 8,3MP CMOS. 4 in 1 output (HDCVI / HDTV / AHD / 960H). 2,8 mm lens (102,2°). ICR filter. OSD, ATW, MWB, AGC, BLC, digital WDR, DNR, brightness, sharpness, mirror. IP67, IK10. 3AXIS. 12V DC
<u>HYU-438</u>	HYU-438		HD-TVI TURBO HD 4.0 fixed dome ULTRAPRO series with IR illumination of 60 m, for outdoors. 8,3MP CMOS. Double video output HD-TVI/CVBS. 2,8 mm fixed lens (102,2°). ICR filter. OSD, ATW, MWB, AGC, BLC, HLC, real WDR 120dB, 3D-DNR, defog, mirror, privacy mask. IP67. 3AXIS. 12V DC
<u>HYU-490</u>	HYU-490		4 in 1 vandal dome PRO series with Smart IR of 60 m, for outdoors. 5MP CMOS. 4 in 1 (HDCVI/HDTV/AHD/960H). 2,7 ~ 13,5 mm (95,7°~29,1°) motorized lens with manual focus. ICR. 0,01 lux. OSD, AWB, AGC, BLC, digital WDR, DNR, brightness, sharpness, mirror. IP67, IK10. 3AXIS. 12V DC.
<u>HYU-572</u>	HYU-572		HD-TVI dome PRO series with Smart IR of 40 m for outdoors. 5MP CMOS. HD-TVI video output. 2,7~13,5 mm motorized lens (95,7°~29,1°). ICR. OSD, ATW, MWB, AGC, BLC, digital WDR, 2D-DNR, image adjustment. IP67. 3AXIS. 12V DC. PoC.at compatible.
<u>HYU-775</u>	HYU-775		4 in 1 HYUNDAI NEXT GEN dome ULTRAPRO series with Smart Light of 20 m for outdoors. 2MP CMOS. 1080P resolution @ 25 / 30ips Switchable 4-in-1 video output. 2.8 mm lens. ICR filter AWB, AGC, BLC, HLC, HLS, WDR 130dB, 2D / 3D-DNR, Anti flicker, motion detection and privacy masks. It incorporates PIR detector, strobe and siren. 1 alarm output IP67 3AXIS. 12V DC
<u>HYU-657</u>	HYU-657		HD-TVI minidome PRO series with Smart IR of 40 m for outdoors. 2MP CMOS. HD-TVI video output. 2,8~12 mm motor lens with autofocus (103°~32,1°). ICR filter. OSD, AWB, AGC, BLC, HLC, WDR 120dB, 3D-DNR, image adjustment, motion detection and privacy mask. IP67. 3AXIS. 12V DC. PoC.at compatible.
<u>HYU-757</u>	HYU-757		4 in 1 HYUNDAI NEXT GEN dome PRO series with 60 m Smart IR for outdoors. 5MP CMOS. 5MP @ 20fps 4-in-1 video output switch. 2.7 ~ 13.5 mm motor lens with autofocus (92.3 ° ~ 29.3 °). ICR filter AWB, AGC, BLC, WDR 130dB, 3D-DNR, motion detection and privacy masks. IP67 3AXIS. 12V DC, 24V AC.

<u>HYU-758</u>	HYU-758		4 in 1 HYUNDAI NEXT GEN dome PRO series with 60 m Smart IR for outdoors. 5MP CMOS. 5MP@20fps 4-in-1 video output switch. 2.7 ~ 13.5 mm (92.3 ° ~ 29.3 °) motor lens with autofocus. ICR filter AWB, AGC, BLC, WDR 130dB, 3D-DNR, video sensor and privacy masks. IP67 3AXIS. 12V DC, 24V AC.
<u>HYU-658</u>	HYU-658		HD-TVI dome PRO series with Smart IR of 60 m, vandal protection for outdoors. 2MP CMOS. HD-TVI video output. 2,7~13,5 mm motorlens with autofocus (103°~32,1°). ICR filter. OSD, AWB, AGC, BLC, HLC, WDR 130dB, 3D-DNR, image adjustment, motion detection and privacy mask. IP67, IK10. 3AXIS. 12V DC. PoC.af compatible.
<u>SAM-4068</u>	SAM-4068		4 in 1 PTZ dome PRO series, 80°/sec. with IR illumination of 20 m, for outdoors. 1/2,9" Sony® CMOS, 2MP @ 1080P. 4 in 1 output switch from UTC controller (HDCVI / HDTV / AHD / CVBS 960H). 3X optical zoom, 2,8~8 mm with autofocus. ICR filter. OSD, AWB, AGC, 2D/3D-DNR, BLC, digital WDR. IP66, Lightning-proof 4KV. 12V DC.
<u>SAM-4499</u>	SAM-4499		4 in 1 dome PRO series with IR of 40 m for outdoors. 1/2,5" CMOS, 8MP. 4 in 1 output (HDCVI / HDTV / AHD / 960H) switch from OSD. ICR filter. 2,8 ~ 12 mm motor lens with autofocus. OSD, AWB, AGC, 2D/3D-DNR, WDR true, Defog, motion detection and privacy mask. IP66. 3AXIS. 12V DC.
<u>SAM-4503</u>	SAM-4503		4 in 1 dome PRO series with IR of 40 m for outdoors. 1/2,5" CMOS, 8MP. 4 in 1 output (HDCVI / HDTV / AHD / 960H) switch from OSD. ICR filter. 2,8 ~ 12 mm motor lens with autofocus. OSD, AWB, AGC, 2D/3D-DNR, WDR true, Defog, motion detection and privacy mask. IP66. 3AXIS. 12V DC.
<u>HYU-592</u>	HYU-592		4 in 1 dome ULTRAPRO series with Smart IR of 60 m for outdoors. 8,3MP CMOS. 4 in 1 output (HDCVI / HDTV / AHD / 960H). 2,7 ~ 13,5 mm motorized lens with autofocus (108,1°~45,6°). ICR filter. OSD, ATW, MWB, AGC, BLC, digital WDR , DNR, brightness, sharpness, mirror. IP67. 3AXIS. 9V~15V DC.
<u>HYU-436</u>	HYU-436		HD-TVI TURBO HD 4.0 fixed dome ULTRAPRO series with IR illumination of 80 m for outdoors. 8,3MP CMOS. Double video output HD-TVI/CVBS. 2,8~12 mm motorized lens (108,1°~45,6°) with autofocus. ICR. OSD, ATW, MWB, AGC, BLC, HLC, real WDR 120dB, 3D-DNR, defog, mirror, privacy mask. IP67. 3AXIS. 12V DC.




Analog Cameras HD/CVBS - Bullet









Reference	Model	Photo	Description
<u>SAM-4546</u>	SAM-4546		4 in 1 AirSpace bullet camera PRO series with IR of 25 m for outdoors. 1/2,9" CMOS, 2MP. 4 in 1 output (HDCVI / HDTV / AHD / 960H) via switch. ICR filter. 2,8 mm lens. OSD, AWB, AGC, BLC, WDR digital, 3D-NR. IP66. 12V DC.

<u>SAM-4323N</u>	SAM-4323N		4 in 1 bullet camera LITE series with Smart IR of 25 m for outdoors. 1/2,7" CMOS, 2MP. 4 in 1 output (HDCVI / HDTVI / AHD / 960H). ICR filter. 2,8 mm fixed lens. OSD, AWB, MWB, AGC, BLC, real WDR, 2D-DNR. IP66. 3AXIS bracket. 12V DC.
<u>HYU-761</u>	HYU-761		4 in 1 HYUNDAI NEXT GEN bullet camera LITE series with Smart IR of 20 m, for outdoors. 2MP CMOS. 4 in 1 video output switch. 2.8 mm (103 °) lens. ICR filter IP66 3AXIS. 12V DC
<u>SAM-4557</u>	SAM-4557		4 in 1 AirSpace bullet camera PRO series with IR of 20 m for outdoors. 1/2,9" Sony CMOS, at 2MP. 4 in 1 output (HDCVI / HDTVI / AHD / 960H) via switch. ICR filter. 2,8 mm lens. OSD, AWB, AGC, BLC, digital WDR, 3D-NR. IP67. 3AXIS. 12V DC.
<u>SAM-4558</u>	SAM-4558		4 in 1 AirSpace bullet camera PRO series with IR of 20 m for outdoors. 1/2,9" Sony CMOS at 2MP. 4 in 1 output (HDCVI / HDTVI / AHD / 960H) from switch. ICR filter. 2,8 mm lens. OSD, AWB, AGC, BLC, digital WDR, 3D-NR. IP67. 3AXIS. 12V DC.
<u>SAM-4608</u>	SAM-4608		4 in 1 bullet camera PRO series with IR of 30 m for outdoors. 1/2,8" CMOS, 2MP. 4 in 1 output (HDCVI / HDTVI / AHD / 960H) switch from OSD. ICR filter. 3,6 mm lens. OSD, AWB, AGC, 2D/3D-DNR, digital WDR, Defog, motion detection and privacy mask. IP66. 3AXIS. 12V DC.
<u>SAM-4609</u>	SAM-4609		4 in 1 bullet camera PRO series with IR of 30 m for outdoors. 1/2,8" CMOS, 2MP. 4 in 1 output (HDCVI / HDTVI / AHD / 960H) switch from OSD. ICR filter. 3,6 mm lens. OSD, AWB, AGC, 2D/3D-DNR, digital WDR, Defog, motion detection and privacy mask. IP66. 3AXIS. 12V DC.
<u>SAM-4573</u>	SAM-4573		4 in 1 AirSpace bullet camera, PRO series with IR of 20 m for outdoors. 1/2,5" Sony CMOS at 5MP. 4 in 1 output (HDCVI / HDTVI / AHD / 960H) from switch. ICR filter. 2,8 mm lens. OSD, AWB, AGC, 2D/3D-DNR, digital WDR. IP67. 3AXIS. 12V DC.
<u>SAM-3441N</u>	SAM-3441N		4 in 1 bullet camera PRO series with IR illumination of 30 m, for outdoors. 1/2,7" Sony Exmor CMOS, 2MP @ 1080P. 4 in 1 output (HDCVI / HDTVI / AHD / 960H). 3,6 mm fixed lens. AWB, AGC, AES, 2D-NR, digital WDR. IP66. 3AXIS 360° bracket. 12V DC.

<u>SAM-4588</u>	SAM-4588		4 in 1 AirSpace dome StarLight Full Color ULTRAPRO series with white illumination of 20 m for outdoors. 1/2.8" Sony STARVIS CMOS, 2MP. 4-in-1 output (HDCVI / HDTV / AHD / 960H) switch. ICR filter 2.8 mm lens. OSD, AWB, AGC, 2D / 3D-DNR, WDR 120dB. IP67 12V DC
<u>HYU-337</u>	HYU-337		4 in 1 bullet camera PRO series with IR illumination up to 30 meters, for outdoors. 1/2,9" Sony CMOS, 2,1 MP @ 1080P. 4 in 1 output (HDCVI / HDTV / AHD / 960H). ICR filter. 2,8 mm fixed lens. OSD, AWB, AGC, AES, 2D/3D-DNR, BLC, HLC, digital WDR, Sense Up, defog, motion detection and privacy mask. IP66. Lightning-proof. Soporte 3AXIS. 12V DC
<u>HYU-513</u>	HYU-513		4 in 1 bullet camera PRO series with Smart IR of 20 m for outdoors. 2MP CMOS. 4 in 1 output (HDCVI / HDTV / AHD / 960H). 2,8 mm fixed lens (103°). ICR filter. OSD, digital WDR. IP66. 3AXIS. 12V DC.
<u>HYU-565</u>	HYU-565		HD-TVI bullet camera PIR series with Smart IR of 20 m and motion detection by active PIR, for outdoors, 2MP CMOS. HD-TVI video output. 2,8 mm lens (103°). 0,01 lux color. ICR. OSD, ATW, AGC, BLC, DNR, mirror and image adjustment. Visual alarm via white led. IP67. 3AXIS bracket. 12V DC.
<u>SAM-4547</u>	SAM-4547		4 in 1 AirSpace bullet camera LITE series with IR of 40 m for outdoors. 1/2,9" CMOS, 2MP. 4 in 1 output (HDCVI / HDTV / AHD / 960H) via switch. ICR filter. 2,7 ~ 13,5 mm varifocal lens. OSD, AWB, AGC, BLC, WDR digital, 3D-NR. IP66. 12V DC.
<u>SAM-4324N</u>	SAM-4324N		4 in 1 bullet camera LITE series with Smart IR of 40 m for outdoors. 1/2,7" CMOS, 2MP. 4 in 1 output (HDCVI / HDTV / AHD / 960H). ICR. 2,8 ~ 12 mm varifocal lens. OSD, AWB, MWB, AGC, BLC, real WDR, 2D-DNR. IP66. 3AXIS bracket. 12V DC.
<u>HYU-150N</u>	HYU-150N		4 in 1 bullet camera LITE series with IR of 40 m, for outdoors. 1/4" CMOS, 1MP @ 720P. 4 in 1 output (HDCVI / HDTV / AHD / 960H). 2,8~12 mm varifocal lens. ICR filter. IP66. 3AXIS. 12V DC.
<u>HYU-249</u>	HYU-249		4 in 1 bullet camera serie PRO series with IR illumination of 40 m, for outdoors. 1/3" Sony CMOS , 2,4MP @ 1080P. 4 in 1 output (HDCVI / HDTV / AHD / 960H). 2,8 mm fixed lens. ICR filter. OSD, AWB, AGC, BLC, HLC, 2D/3D-DNR. IP66. 3AXIS brakcet. 12V DC.

<u>SAM-4592</u>	SAM-4592		4 in 1 AirSpace bullet camera StarLight Full Color ULTRAPRO series with white illumination of 20 m for outdoors. 1/2,8" Sony STARVIS CMOS, 2MP. 4 in 1 output (HDCVI / HDTV / AHD / 960H) via switch. ICR filter. 2,8 mm lens. OSD, AWB, AGC, 2D/3D-DNR, WDR 120dB. IP67. 12V DC.
<u>HYU-481</u>	HYU-481		HD-TVI bullet camera PIR series with Smart IR of 20 m and motion detection by active PIR, for outdoors. 2MP CMOS. HD-TVI video output. 2,8 mm fixed lens (103,5°). 0,005 lux. ICR filter. OSD, ATW, MWB, AGC, BLC, real WDR 120dB, 3D-DNR, mirror, motion detection and privacy mask. Visual alarm by white led. IP67. 3AXIS bracket. 12V DC.
<u>SAM-4560</u>	SAM-4560		4 in 1 AirSpace bullet camera PRO series with IR of 40 meters for outdoors. 1/2,9" Sony CMOS at 2MP. 4 in 1 output (HDCVI / HDTV / AHD / 960H) from switch. ICR filter. 2,8 mm lens. OSD, AWB, AGC, BLC, digital WDR, 3D-NR. IP67. 3AXIS. 12V DC.
<u>SAM-4571</u>	SAM-4571		4 in 1 AirSpace bullet camera PRO series with IR of 40 m for outdoors. 1/2,9" Sony CMOS, 2MP. 4 in 1 output (HDCVI / HDTV / AHD / 960H) switch. ICR filter 2.7 ~ 13.5 mm varifocal lens. OSD, AWB, AGC, BLC, digital WDR, 3D-NR. IP67 12V DC
<u>SAM-4559</u>	SAM-4559		4 in 1 AirSpace bullet camera PRO series with IR of 40 m for outdoors. 1/2,9" Sony CMOS at 2MP. 4 in 1 output (HDCVI / HDTV / AHD / 960H) switch. ICR filter 2.7 ~ 13.5 mm varifocal lens. OSD, AWB, AGC, BLC, digital WDR, 3D-NR. IP67 12V DC.
<u>SAM-4580</u>	SAM-4580		4 in 1 AirSpace bullet camera LITE series with IR of 20 m for outdoors. 1/2,7" CMOS, 8MP. 4 in 1 output (HDCVI / HDTV / AHD / 960H) switch. ICR filter 2.8 mm lens. OSD, AWB, AGC, BLC, 3D-DNR, privacy mask. IP67 12V DC
<u>SAM-4581</u>	SAM-4581		4 in 1 AirSpace bullet camera LITE series with IR of 25 m for outdoors. 1/2,7" CMOS, 8MP. 4-in-1 output (HDCVI / HDTV / AHD / 960H) switch. ICR filter 2.8 mm lens. OSD, AWB, AGC, BLC, 3D-DNR, privacy mask. IP67 12V DC
<u>SAM-4332</u>	SAM-4332		4 in 1 bullet camera PRO series with Smart IR of 40 m for outdoors. 1/2,9" Sony CMOS, 2MP. 4 in 1 output (HDCVI / HDTV / AHD / 960H). ICR filter. 2,8 ~ 12 mm varifocal lens. OSD, AWB, MWB, AGC, BLC, real WDR, 2D-DNR. IP66. 12V DC.

<u>SAM-4333</u>	SAM-4333		4 in 1 bullet camera PRO series with Smart IR of 40 m for outdoors. 1/2,9" Sony CMOS, 2MP. 4 in 1 output (HDCVI / HDTV / AHD / 960H). ICR. 2,8 ~ 12 mm varifocal lens. OSD, AWB, MWB, AGC, BLC, real WDR, 2D-DNR. IP66. 12V DC.
<u>SAM-4225</u>	SAM-4225		4 in 1 bullet camera PRO series with IR of 40 m for outdoors. 1/2,7" CMOS, 5MP. 4 in 1 output (HDCVI @ 4MP, HDTV @ 5MP/4MP, AHD @ 5MP/4MP, CVBS @ 960H), 3,6 mm fixed lens. AWB, AGC, AES, 2D-NR. IP66. 3AXIS bracket. 12V DC.
<u>HYU-244</u>	HYU-244		4 in 1 bullet camera PRO series with IR illuminatio of 40 meters, for outdoors. 1/3" CMOS, 3 MP. 4 in 1 output via DIP switch (HDCVI @1080P / HDTV @3MP / AHD @3MP / CVBS @960H). ICR. 2,8 ~ 12 mm varifocal lens. OSD, AWB, MWB, AGC, AES, 2D-DNR, BLC, WDR real. IP66. 3AXIS bracket. 12V DC.
<u>HYU-569</u>	HYU-569		HD-TVI bullet camera PRO series with Smart IR of 20 m for outdoors. 5MP CMOS. HD-TVI video output. 2,8 mm lens (85,5°). ICR. OSD, ATW, MWB, AGC, BLC, digital WDR, 2D-DNR, image adjustment. IP67. 3AXIS bracket. 12V DC. PoC.af. compatible
<u>HYU-335</u>	HYU-335		4 in 1 bullet camera PRO series with IR illumination of 40 meters, for outdoors. 1/2,9" Sony CMOS, 2 MP @ 1080P. 4 in 1 output (HDCVI / HDTV / AHD / 960H). ICR filter. 2,8 ~ 12 mm varifocal lens. OSD, AWB, AGC, AES, 2D/3D-DNR, BLC, digital WDR, Sense Up, defog, motion detection and privacy mask. IP66. Lightning-proof. 3AXIS bracket. 12V DC.
<u>SAM-4610</u>	SAM-4610		4 in 1 bullet camera PRO series with IR of 60 m for outdoors. 1/2,8" CMOS, 2MP. 4 in 1 output (HDCVI / HDTV / AHD / 960H) with OSD switch. ICR filter. 2,7 ~ 13,5 mm varifocal lens. OSD, AWB, AGC, 2D/3D-DNR, WDR true, Defog, motion detection and privacy mask. IP66. 3AXIS. 12V DC.
<u>SAM-4612</u>	SAM-4612		4 in 1 bullet camera PRO series with IR of 60 m for outdoors. 1/2,8" CMOS, 2MP. 4 in 1 output (HDCVI / HDTV / AHD / 960H) switch OSD. ICR filter. 2,7 ~ 13,5 mm varifocal lens. OSD, AWB, AGC, 2D/3D-DNR, WDR true, Defog, motino detection and privacy mask. IP66. 3AXIS. 12V DC.
<u>SAM-4325</u>	SAM-4325		4 in 1 bullet camera PRO series with IR illumination of 40 m for outdoors. 1/2,7" CMOS, 2 MP. 4 in 1 output (HDCVI / HDTV / AHD / 960H). ICR filter. 2,8~12 mm motorized lens. OSD, AWB/MWB, AGC, 2D-DNR, BLC, digital WDR. IP66. 3AXIS bracket. 12V DC.

<u>HYU-776</u>	HYU-776		
<u>HYU-55N</u>	HYU-55N		4 in 1 dome PRO series with Smart IR of 40 m for outdoors. 2MP CMOS. 4 in 1 output (HDCVI / HDTV / AHD / 960H). 2,8 ~ 12 mm varifocal lens (102,25°~32°). ICR filter. OSD, ATW/MWB, AGC, BLC, digital WDR. IP66. 3AXIS. 12V DC.
<u>SAM-4335</u>	SAM-4335		4 in 1 bullet camera PRO series with IR illumination of 40 m for outdoors. 1/2,9" Sony CMOS, 2 MP. 4 in 1 output (HDCVI / HDTV / AHD / 960H). ICR filter. 2,7~13,5 mm motorized lens. OSD, AWB, AGC, DNR, digital WDR. IP66. 3AXIS bracket. 12V DC
<u>SAM-4611</u>	SAM-4611		4 in 1 bullet camera PRO series with IR of 60 m for outdoors. 1/2,8" CMOS, 2MP. 4 in 1 output (HDCVI / HDTV / AHD / 960H) switch OSD. ICR filter. 2,7 ~ 13,5 mm motor lens with autofocus. OSD, AWB, AGC, 2D/3D-DNR, WDR true, Defog, motion detection and privacy mask. IP66. 3AXIS. 12V DC.
<u>SAM-4613</u>	SAM-4613		4 in 1 bullet camera PRO series with IR of 60 m for outdoors. 1/2,8" CMOS, 2MP. 4 in 1 output (HDCVI / HDTV / AHD / 960H) switch OSD. ICR filter. 2,7 ~ 13,5 mm motor lens with autofocus. OSD, AWB, AGC, 2D/3D-DNR, WDR true, Defog, motion detection and privacy mask. IP66. 3AXIS. 12V DC.
<u>HYU-165N</u>	HYU-165N		4 in 1 bullet camera PRO series with IR illumination of 50 meters, for outdoors. 1/2.9" Sony CMOS. 2MP @ 1080p. 4 in 1 output with DIP switch (HDCVI / HDTV / AHD / 960H). Black tempered glass. 2.7~13.5 mm motorized lens with improved autofocus (synchronous focus). ICR. OSD, AWB, AGC, AES, ATR, 2D-NR, digital WDR. IP66. 3AXIS bracket. 12V DC
<u>HYU-805</u>	HYU-805		
<u>HYU-674</u>	HYU-674		NightFighter 4 in 1 bullet camera with STARLIGHT technology and Smart IR of 70 m for outdoors. 2MP CMOS. 4 in 1 video output switch. 2,7 ~ 13,5 mm motorized lens (102°~31°). ICR filter. OSD, AWB, AGC, BLC, HLC, WDR 120dB, 3D-DNR, image adjustment. IP67. 3AXIS. 12V DC.



<u>HYU-762</u>	HYU-762		NightFighter 4 in 1 bullet camera with STARLIGHT technology and Smart IR of 70 m for outdoors. 2MP CMOS. 4 in 1 video output switch. 2,7 ~ 13,5 mm motorized lens (102°~31°). ICR filter. OSD, AWB, AGC, BLC, HLC, WDR 120dB, 3D-DNR, image adjustment. IP67. 3AXIS. 12V DC.
<u>SAM-4251</u>	SAM-4251		4 in 1 bullet camera PRO series with IR of 50 m for outdoors. 1/2,7" CMOS @ 1080P. 4 in 1 output (HDCVI / HDTV / AHD / 960H) by switch. ICR. 2,7 ~ 13,5 mm motorized lens. OSD, AWB, AGC, AES, 2D/3D-DNR, digital WDR, motion detection and privacy mask. IP66. 3AXIS bracket. 12V DC.
<u>HYU-585</u>	HYU-585		4 in 1 bullet camera Color View series with white illumination of 20 meters for outdoors. 2MP CMOS. 4 in 1 output (HDCVI / HDTV / AHD / 960H). 3,6 mm lens (83,6°). 24 hour color mode (no switch to B/W). OSD, ATW/MWB, AGC, BLC, real WDR 120dB, 3D-DNR, image adjustment, mirror mode, motion detection and privacy mask. IP67. 3AXIS. 12V DC.
<u>SAM-4615</u>	SAM-4615		4 in 1 bullet camera PRO series with IR of 80 m for outdoors. 1/2,8" CMOS, 2MP. 4 in 1 output (HDCVI / HDTV / AHD / 960H) switch OSD. ICR filter. 2,7 ~ 13,5 mm motor lens with autofocus. OSD, AWB, AGC, 2D/3D-DNR, WDR true, Defog, motion detection and privacy mask. IP66. 3AXIS. 12V DC.
<u>SAM-4509</u>	SAM-4509		4 in 1 bullet camera PRO series with IR illumination of 50 m for outdoors. 1/2,8" CMOS, 5MP. 4 in 1 output (HDCVI / HDTV / AHD / 960H) from switch OSD. ICR filter. 2,8 ~ 13,5 mm varifocal lens. OSD, AWB, AGC, 2D/3D-DNR, WDR true, Defog, motion detection and privacy mask. IP66. 3AXIS. 12V DC.
<u>HYU-388</u>	HYU-388		HD-TVI bullet camera PRO series with Smart IR of 40 m for outdoors. 2MP CMOS. HD-TVI video output. 2,7 ~ 12 mm varifocal lens (102,5°~32°). ICR filter. ATW, AGC, DNR. IP66. 3AXIS bracket. 12V DC. PoC compatible.
<u>HYU-587</u>	HYU-587		4 in 1 bullet camera PRO series with Smart IR of 30 m for outdoors. 8,3MP CMOS. 4 in 1 output (HDCVI / HDTV / AHD / 960H). 2,8 mm lens (102,2°). ICR filter. OSD, ATW, MWB, AGC, BLC, digital WDR, DNR, brightness, sharpness, mirror. IP67. 3AXIS. 12V DC.
<u>SAM-4508</u>	SAM-4508		4 in 1 bullet camera PRO series with IR of 50 m for outdoors. 1/2,8" CMOS, 2MP. 4 in 1 output (HDCVI / HDTV / AHD / 960H) from switch OSD. ICR filter. 2,7 ~ 13,5 mm motor lens. OSD, AWB, AGC, 2D/3D-DNR, WDR true, Defog, motion detection and privacy mask. IP66. 3AXIS. 12V DC.

<u>SAM-4504</u>	SAM-4504		4 in 1 bullet PRO series with IR of 35 m for outdoors. 1/2,8" CMOS at 5MP. 4 in 1 output (HDCVI / HDTVI / AHD / 960H) switch from OSD. ICR filter. 2,8 ~ 13,5 mm motor lens with autofocus. OSD, AWB, AGC, 2D/3D-DNR, WDR true, Defog, motion detection and privacy mask. IP66. 3AXIS. 12V DC.
<u>HYU-437</u>	HYU-437		HD-TVI TURBO HD 4.0 bullet camera ULTRAPRO series with IR illumination of 40 m for outdoors. 8,3MP CMOS. Double video output HD-TVI/CVBS. 2,8 mm fixed lens (102,2°). ICR filter. OSD, ATW, MWB, AGC, BLC, HLC, real WDR 120dB, 3D-DNR, defog, mirror, privacy mask. IP67. 3AXIS bracket. 12V DC.
<u>HYU-763</u>	HYU-763		4-in-1 HYUNDAI NEXT GEN bullet camera PRO series with Smart IR of 80 m, for outdoors. 5MP CMOS. 5MP @ 20fps 4-in-1 video output switch. 2.7 ~ 13.5 mm motor lens with autofocus (92.3 ° ~ 29.3 °). ICR filter AWB, AGC, BLC, WDR 130dB, 3D-DNR, motion detection and privacy masks. IP67 3AXIS. 12V DC, 24V AC.
<u>SAM-2974N</u>	SAM-2974N		4 in 1 bullet camera PRO series with IR illumination of 100 meters, for outdoors. 1/2.7" Lowlight CMOS, 2.4MP @ 1080p. 4 in 1 output (HDCVI/HDTVI/AHD/960H). 5~50 mm varifocal lens. ICR. OSD, AWB, AGC, AES, 2D-NR, digital WDR. IP66. 3AXIS. 12V DC.
<u>HYU-590</u>	HYU-590		4 in 1 bullet camera ULTRAPRO series with Smart IR of 80 m for outdoors. 8,3MP CMOS. 4 in 1 output (HDCVI / HDTVI / AHD / 960H). 2,7 ~ 13,5 mm motor lens with autofocus (108,1°~45,6°). ICR filter. OSD, ATW, MWB, AGC, BLC, digital WDR, DNR, brightness, sharpness, mirror. IP67. 3AXIS. 9V~15V DC.
<u>HYU-530</u>	HYU-530		HD-TVI Starlight bullet camera with Smart IR of 110 m for outdoors. CMOS, 2MP. Dual video output HD-TVI/CVBS. 5~50 mm (59,8°~6,2°) motorized lens with autofocus. 62X digital zoom. ICR. OSD, ATW, AGC, BLC, real WDR 120dB, 3D-DNR, defog, mirror, motion detection and privacy mask. IP66. Calefactor. 3AXIS bracket. 24V AC / 12V DC.



Analog Cameras HD/CVBS - PTZ Dome

Reference	Model	Photo	Description
<u>SAM-4049</u>	SAM-4049		4 in 1 PTZ dome, 200°/sec. with IR illumination of 50 m, for outdoors. 1/3" Sony CMOS, 2MP @ 1080P. 4 in 1 output (HDCVI / HDTVI / AHD / 960H). 10X optical zoom, 5,1~51 mm (51,8°~5,86°). ICR. 0,1/0,01 lux. OSD, AWB, BLC, digital WDR. Idle mode . 220 presets. RS485. IP66. Lightning-proof 6KV. Bracket and power supply included. 12V DC.
<u>HYU-456</u>	HYU-456		4 in 1 PTZ dome PRO series of 180°/sec. with IR of 100 m for outdoors. 1/2,9" Sony CMOS, 2MP at 1080P. 4 in 1 output (HDCVI / HDTVI / AHD / 960H). 10X optical zoom 5,1~51 mm (54°~4,9°). ICR filter. 0,05/0,01 lux. OSD, AWB, AGC, BLC, digital WDR, 2D/3D-DNR, mirror, flip, defog. 256 presets. RS485. IP66. Lightning-proof. 12V DC. 4".



Analog Cameras HD/CVBS - Positioning Systems









Reference	Model	Photo	Description
<u>HYU-454</u>	HYU-454		4 in 1 PTZ bullet camera PRO series with IR of 30~40 m for outdoors. 1/2,7 CMOS, 2 MP. 1080P resolution. 4 in 1 output (HDCVI / HDTV1 / AHD / 960H) by DIP switch. ICR filter. 0,1/0,01 lux. 4X optical zoom (2,8~12 mm). OSD, AWB, AGC, 2D/3D-DNR, mirror. 180° positioner. 1 preset. IP65. 12V DC.
<u>HYU-113N</u>	HYU-113N		HD-TVI bullet PTZ camera PRO series with IR illumination of 50 m, for outdoors. 1/2,8" Sony CMOS, 2MP @ 1080P. 4 in 1 output (HDCVI / HDTV1 / AHD / 960H) switch by RS485 (Pelco-D). 2,8~12 mm motorized lens. ICR dual filter. OSD, BLC, real WDR, ROI. 250° positioner. 255 presets. Pelco, RS485. IP66. Lightning-proof. 12V DC









Analog Cameras HD/CVBS - Hidden & Mini Cameras









Reference	Model	Photo	Description
<u>SAM-1478</u>	SAM-1478		AirSpace® hidden camera inside a smoke detector. 1/3" Sony® Super HAD II CCD. 600 lines. 0.1 lux. 4 mm lens. AGC. 12V DC.
<u>HYU-483</u>	HYU-483		HD-TVI compact camera PIR series with Smart IR of 20 m and motion detection by active PIR, for indoors. 2MP CMOS. HD-TVI video output. 2,8 mm fixed lens (103,5°). 0,005 lux. ICR filter. OSD, ATW, MWB, AGC, BLC, real WDR 120dB, 3D-DNR, mirror, motion detection and privacy mask. 2 way audio (built in microphone). 12V DC







Analog Recorders HD/CVBS - Analog Recorders

Reference	Model	Photo	Description
<u>HYU-778</u>	ZVR4104P-2MLITE-AUDIO		
<u>HYU-781</u>	ZVR4104M-A-2MLITE-AUDIO		



<u>HYU-370</u>	ZVR5104M-4MLITE		4 channel 5 in 1 ZVR HDCVI/HDTVII/AHD/CVBS + 1 IP channel. H.265+/H265/H.264+/H264. 2 way audio. 4 channel playback at 1080P. Recording: 4M-N, 3MP (channel1, 15 fps, only TVI), 4MP (1 IP input), 1080P (15 fps), 1080N, 720P, 960H, D1/4CIF, VGA, CIF, QVGA, QCIF (25 fps). BNC output at D1/4CIF. HDMI and VGA output at 1080P. 1 HDD SATA. Onvif, P2P, DDNS. 2 USB, 1 RS485. 12V DC.
<u>HYU-790</u>	ZVR5104M-4MLITE-AUDIO		4 channel 5 in 1 HYUNDAI ZVR HDCVI/HDTVII/AHD/CVBS + 2 IP channels. H.265 Pro+, H265 Pro, H.265, H.264+, H.264. 2 way audio. 4 channel Synchronous playback. Recording: 4MP, 1080P, 720P, 960H, D1/4CIF, VGA, CIF, QVGA, QCIF (25 fps). Salidas HDMI (4K) and VGA (1080P) simultaneous. BNC output at D1/4CIF. 1 HDD SATA capacity. Onvif, P2P, DDNS. 2 USB, 1 RS485. 12V DC.
<u>HYU-784</u>	ZVR5104P-4MLITE-AUDIO		4 channel 5 in 1 HYUNDAI ZVR HDCVI/HDTVII/AHD/CVBS + 2 IP channels. H.265 Pro+, H265 Pro, H.265, H.264+, H.264. 2 way audio. Synchronous playback of 4 channels. 4MP, 1080P, 720P, 960H, D1/4CIF, VGA, CIF, QVGA, QCIF (25 ips). HDMI (4K) and VGA (1080P) simultaneous output. BNC output at D1/4CIF. 1 HDD SATA. Onvif, P2P, DDNS. 2 USB, 1 RS485. 12V DC.
<u>HYU-779</u>	ZVR4108P-2MLITE-AUDIO		8 channel 5 in 1 ZVR HDCVI/HDTVII/AHD/CVBS + 2 IP channels 1080P. H.264+/H264. 2 way audio. 8 channel playback at 720P. Recording: 1080N, 720P, WD1, D1, VGA, CIF, QVGA, QCIF. HDMI and VGA simultaneous output at 1080P. 1 HDD SATA. RJ45 Fast Ethernet. Onvif, P2P, DDNS. 2 USB. 12V DC.
<u>HYU-793</u>	ZVR5104M-A-4MLITE-AUDIO		4 channel 5 in 1 HYUNDAI ZVR HDCVI/HDTVII/AHD/CVBS + 2 IP channel. H.265 Pro+, H265 Pro, H.265, H.264+, H.264. 2 way audio. Alarm: 4 in / 8 out. 4 channel synchronous playback. Recording 4MP, 1080P, 720P, 960H, D1/4CIF, VGA, CIF, QVGA, QCIF (25 fps). HDMI (4K) and VGA (1080P) simultaneous output. BNC output at D1/4CIF. 1 HDD SATA. Onvif, P2P, DDNS. 2 USB, 1 RS485. 12V DC.
<u>HYU-373</u>	ZVR5104M-A-4MLITE		4 channel 5 in 1 ZVR, HDCVI/HDTVII/AHD/CVBS + 1 IP channel. H.265+/H265/H.264+/H264. 2 way audio. 4 channel playback at 1080P. Recording: 4M-N, 3MP (channel 1, 15 fps, only TVI), 4MP (1 IP input), 1080P (15 fps), 1080N, 720P, 960H, D1/4CIF, VGA, CIF, QVGA, QCIF (25 fps). BNC output at D1/4CIF. HDMI and VGA output at 1080P. Alarm: 4 in / 1 out. 1 HDD SATA capacity. Onvif, P2P, DDNS. 2 USB, 1 RS485. 12V DC.
<u>HYU-782</u>	ZVR4108M-A-2MLITE-AUDIO		
<u>HYU-371</u>	ZVR5108M-4MLITE		8 channel 5 in 1 ZVR HDCVI/HDTVII/AHD/CVBS + 2 IP channel. H.265+/H265/H.264+/H264. 2 way audio. 8 channel playback at 1080P. Recording: 4M-N, 3MP (channel1 & 2, 15 fps, only TVI), 4MP (2 IP input), 1080P (15 fps), 1080N, 720P, 960H, D1/4CIF, VGA, CIF, QVGA, QCIF (25 fps). BNC output at D1/4CIF. HDMI and VGA output at 1080P. 1 HDD SATA. Onvif, P2P, DDNS. 2 USB, 1 RS485. 12V DC.

<u>HYU-580</u>	AI-ZVR5104M-4MLITE		4 channel 5 in 1 ZVR HDCVI/HDTV/ AHD/ CVBS + 2 IP channels. H.265 Pro+, H265 Pro, H.265, H.264+, H.264. 2 way audio. 4 channel simultaneous playback. Recording: 6MP (only IP), 4M-N, 3MP (channel 1, 15 fps, only TVI/AHD), 1080P (15 fps), 1080N, 720P, 960H, D1/4CIF, VGA, CIF, QVGA, QCIF (25 fps). HDMI and VGA simultaneous output at 1080P. BNC output at D1/4CIF. 1 HDD SATA. Onvif, P2P, DDNS. 2 USB, 1 RS485. 12V DC.
<u>HYU-791</u>	ZVR5108M-4MLITE-AUDIO		
<u>HYU-391N</u>	ZVR5104M-POC		4 channel 5 in 1 ZVR HDCVI/HDTV/ AHD/ CVBS + 1 IP channels. H.265+/H265/H.264+/H264. 2 way audio. 4 channel playback 1080P. Recording 3MP (channels 1 to 4, 15 fps, only TVI), 4MP (2 IP inputs), 1080P (15 fps), 1080N, 720P, 960H, D1/4CIF, VGA, CIF, QVGA, QCIF (25 fps). BNC output at D1/4CIF. HDMI and VGA at 1080P. 1 HDD SATA capacity. RJ45 Gigabit. Onvif, P2P, DDNS. 2 USB, 1 RS485. DC48V. Compatible with PoC up to 5MP.
<u>HYU-384N</u>	ZVR5108P-4M-A-LITE		Dahua PTZ IP dome StarLight AI series of 200 /sec. with IR lighting of 100 m, for outdoor. Supports 4G H.265 + / H.265 / H.264 + / H.264 / MJPEG format. 1/2.8" Sony® STARVIS™ CMOS 4 MP. Triple stream. Resolution up to 4MP @ 25ips. 25X optical zoom of 4.8 ~ 120 mm. 16X digital zoom ICR filter 0.005 / 0.0005 lux. OSD, AWB, AGC, BLC, HLC, WDR 120dB, 2D / 3D-DNR, digital defog, EIS, motion detection, privacy masks. Perimeter protection, video motion detection, facial detection, intelligent
<u>HYU-780</u>	ZVR4116P-2MLITE-AUDIO		
<u>HYU-799</u>	ZVR7104-A-5M-AUDIO		4 channel 5 in 1 ZVR HDCVI/HDTV/ AHD/ CVBS + 4 IP ch. H.265 Pro+, H265 Pro, H.265, H.264+, H.264. Audio: 1 in / 1 out. Alarm: 4 in / 1 out. 4 channel synchronous playback. Recording: 8M-N (8 fps, only TVI/IP), 5MP (12 fps, only TVI/AHD), 4MP (15 fps), 3MP (18 fps), 1080P, 720P, 960H, D1/4CIF, VGA, CIF, QVGA, QCIF (25 fps). HDMI (4K, 2K) and VGA (1080P) simultaneous output. BNC output at D1/4CIF. 1 HDD SATA. Onvif, P2P, DDNS. 2 USB, 1 RS485. 12V DC.
<u>HYU-796</u>	AI-ZVR7104-5M-AUDIO		4 channel 5 in 1 HYUNDAI ZVR AiSense series of HDCVI / HDTV / AHD / CVBS + 2 IP channels. Video formats H.265 Pro +, H265 Pro, H.265, H.264 +, H.264. Bidirectional audio. 4 CH synchronized playback. Recording 8MP (8 fps, TVI / IP only), 5MP (12 fps), 4MP (15 fps), 3MP (18 fps), 1080P, 720P, 960H, D1 / 4CIF, VGA, CIF, QVGA, QCIF (25 fps). Simultaneous HDMI (2K) and VGA (1080P) outputs. BNC output to D1 / 4CIF. Capacity of 1 SATA HDD. Onvif, P2P, DDNS. 2 USB, 1 RS485. 12V DC.
<u>HYU-562</u>	ZVR7104-A-POC		4 channel 5 in 1 ZVR HDCVI/HDTV/ AHD/ CVBS + 2 IP channel. H.265+/H265/H.264+/H264. Audio: 4 input / 1 output. 4 channel simultaneous playback. Recording: 6MP (IP), 5MP (TVI, AHD), 4MP, 1080P, 720P, WD1, 4CIF, VGA, CIF. BNC output at 4CIF. HDMI and VGA at 1080P. Alarm: 4 input / 1 output. 1 HDD SATA. Onvif, P2P, DDNS. 2 USB, 1 RS485. 48V DC. Compatible with PoC up to 5MP

<u>HYU-581</u>	AI-ZVR5108M-4MLITE		8 ch 5 in 1 ZVR HDCVI/HDTVI/AHD/CVBS + 4 IP channels. H.265 Pro+, H265 Pro, H.265, H.264+, H.264. 2 way audio. 8 channel simultaneous playback. Recording: 6MP (only IP), 4M-N, 3MP (channels 1 and 2, 15 fps, only TVI/AHD), 1080P (15 fps), 1080N, 720P, 960H, D1/4CIF, VGA, CIF, QVGA, QCIF (25 fps). HDMI and VGA simultaneous output at 1080P. BNC output at D1/4CIF. 1 HDD SATA. Onvif, P2P, DDNS. 2 USB, 1 RS485. 12V DC.
<u>HYU-583</u>	AI-ZVR7104-5M		4 channel 5 in 1 ZVR HDCVI/HDTVI/AHD/CVBS + 4 IP channels. H.265 Pro+, H265 Pro, H.265, H.264+, H.264. Audio: 4 in / 1 out. 4 channel synchronized playback. Recording: 8MP (only IP), 5MP (12 fps, only TVI/AHD), 4MP (15 fps), 3MP (18 fps), 1080P, 720P, 960H, D1/4CIF, VGA, CIF, QVGA, QCIF (25 fps). HDMI and VGA simultaneous output at 1080P. BNC output at D1/4CIF. Alarm: 4 in / 1 out. 1 HDD SATA. Onvif, P2P, DDNS. 2 USB, 1 RS485. 12V DC.
<u>HYU-800</u>	ZVR7208-A-4KLITE-AUDIO		8 channel 5 in 1 ZVR HDCVI/HDTVI/AHD/CVBS + 8 IP channels. H.265 Pro+, H265 Pro, H.265, H.264+, H.264. Audio: 1 in / 1 out. Alarm: 8 in / 1 out. Synchronous playback of 8 channels. 8M-N (8 fps, only TVI/IP), 5MP (12 fps, only TVI/AHD), 4MP (15 fps), 3MP (18 fps), 1080P, 720P, 960H, D1/4CIF, VGA, CIF, QVGA, QCIF (25 fps). HDMI (4K, 2K) and VGA (1080P) simultaneous output. BNC output at D1/4CIF. 1 HDD SATA. Onvif, P2P, DDNS. 2 USB, 1 RS485. 12V DC.
<u>HYU-792</u>	ZVR5116M-4MLITE-AUDIO		16 channel 5 in 1 HYUNDAI ZVR HDCVI/HDTVI/AHD/CVBS + 8 IP channels. H.265 Pro+, H265 Pro, H.265, H.264+, H.264. 2 way audio. 16 channel synchronous playback. Recording: 4MP, 1080P, 720P, 960H, D1/4CIF, VGA, CIF, QVGA, QCIF (25 fps). HDMI (4K) and VGA (1080P) simultaneous output. BNC output at D1/4CIF. 1 HDD SATA. Onvif, P2P, DDNS. 2 USB, 1 RS485. 12V DC.
<u>HYU-379</u>	ZVR8104-A-4K		4 channel 5 in 1 TURBO HD 4.0 ZVR, 8MP (10FPS) / 5MP (20FPS) / 4MP (25FPS) / 3MP (18FPS) / 1080P (25FPS) HDCVI/HDTVI/AHD/CVBS + 2 IP channels at 8MP. H.265+/H.265/H.264+/H.264. Audio: 4 in / 1 out (2 way audio). Recording 8MP/5MP/4MP/3MP (TVI), 1080P/720P (CVI, AHD), WD1/4CIF/VGA/CIF (CVBS), full 4MP in all cameras. BNC a@ 4CIF output. HDMI (4K, 2K) and VGA (1080P) output. 1 HDD SATA capacity. RJ45 Gigabit. Onvif, P2P, DDNS. 1 USB, 2 12V DC.
<u>HYU-375</u>	ZVR5116M-A-4MLITE		16 channel ZVR 5 in 1 HDCVI/HDTVI/AHD/CVBS + 2 IP channels. H.265+/H265/H.264+/H.264. 2 way audio. 16 channel playback at 1080P. Recording 4M-N, 3MP (channel 1 to 4, 15 fps, only TVI), 4MP (2 IP inputs), 1080P (15 fps), 1080N, 720P, 960H, D1/4CIF, VGA, CIF, QVGA, QCIF (25 fps). BNC output at D1/4CIF. HDMI output at 4K and VGA output at 1080P. Alarm: 16 in / 1 out. 1 HDD SATA capacity. RJ45 Gigabit. Onvif, P2P, DDNS. 2 USB, 1 RS485. 12V DC.
<u>HYU-795</u>	ZVR5116M-A-4MLITE-AUDIO		16 channel 5 in 1 HYUNDAI ZVR HDCVI/HDTVI/AHD/CVBS + 8 IP channels. H.265 Pro+, H265 Pro, H.265, H.264+, H.264. 2 way audio. Alarm: 4 in / 8 out. 16 channel synchronous playback. Recording: 4MP, 1080P, 720P, 960H, D1/4CIF, VGA, CIF, QVGA, QCIF (25 fps). HDMI (4K) and VGA (1080P) simultaneous output. BNC output at D1/4CIF. 1 HDD SATA. Onvif, P2P, DDNS. 2 USB, 1 RS485. 12V DC.
<u>HYU-584</u>	AI-ZVR7108-4KLITE		8 channel 5 in 1 ZVR HDCVI/HDTVI/AHD/CVBS + 8 IP channels. H.265 Pro+, H265 Pro, H.265, H.264+, H.264. Audio: 4 in / 1 out. Synchronized playback of 8 channels. Recording: 8MP (8 fps, only TVI/IP), 5MP (12 fps, only TVI/AHD), 4MP (15 fps), 3MP (18 fps), 1080P, 720P, 960H, D1/4CIF, VGA, CIF, QVGA, QCIF (25 fps). HDMI (4K, 2K) and VGA (1080P) simultaneous. BNC output at D1/4CIF. Alarm: 8 in / 4 out. 1 HDD SATA. Onvif, P2P, DDNS. 2 USB, 1 RS485. 12V DC.







<u>HYU-764</u>	ZVR7116-A-4KLITE		16 ch 5 in 1 ZVR HDCVI/HDTV/AHD/CVBS + 16 IP ch. Video formats H.265 Pro +, H.265 Pro, H.265, H.264 +, H.264. Audio: 4 in / 1 out. Synchronized playback of 16 channels. Recording 8M-N (8 fps, only TVI / IP), 5MP (12 fps, only TVI / AHD), 4MP (15 fps), 3MP (18 fps), 1080P, 720P, 960H, D1 / 4CIF, VGA, CIF, QVGA, QCIF (25 fps). Simultaneous HDMI (4K, 2K) and VGA (1080P) outputs. BNC output to D1 / 4CIF. Capacity of 1 SATA HDD. Onvif, P2P, DDNS. 2 USB, 1 RS485. 12V DC.
<u>HYU-563</u>	ZVR7208-A-POC		8 channel 5 in 1 ZVR HDCVI/HDTV/AHD/CVBS + 4 IP channels. H.265+/H265/H.264+/H264. Audio: 4 in / 1 out. 8 channel simultaneous playback. Recording: 8MP (IP), 6MP (TVI, AHD), 4MP, 1080P, 720P, WD1, 4CIF, VGA, CIF. BNC output at 4CIF. HDMI and VGA output at 1080P. Alarm: 8 in / 4 out. 2 HDD SATA. Onvif, P2P, DDNS. 2 USB, 1 RS485. 48V DC. PoC up to 5MP.
<u>HYU-582</u>	AI-ZVR5116M-4MLITE		16 channel 5 in 1 ZVR HDCVI/HDTV/AHD/CVBS + 8 IP channels. H.265 Pro+, H.265 Pro, H.265, H.264+, H.264. 2 way audio. Simultaneous playback of 8 channels. Recording: 6MP (only IP), 4M-N, 3MP (channels 1, 2, 3 and 4, 15 fps, only TVI/AHD), 1080P (15 fps), 1080N, 720P, 960H, D1/4CIF, VGA, CIF, QVGA, QCIF (25 fps). HDMI and VGA simultaneous output at 1080P. BNC output at D1/4CIF. 1 HDD SATA. RJ45 Gigabit. Onvif, P2P, DDNS. 2 USB, 1 RS485. 12V DC.
<u>HYU-380</u>	ZVR8208-A-4K		8 channel 5 in 1 TURBO HD 4.0 ZVR 8MP (10FPS) / 5MP (20FPS) / 4MP (25FPS) / 3MP (18FPS) / 1080P (25FPS) HDCVI/HDTV/AHD/CVBS + 2 IP channel up to 8MP. H.265+/H.265/H.264+/H264. Audio: 8 in / 1 out (2 way audio). Recording: 8MP/5MP/4MP/3MP (TVI), 1080P/720P (CVI, AHD), WD1/4CIF/VGA/CIF (CVBS), full 4MP in all cameras. BNC output @ 4CIF. HDMI (4K, 2K) and VGA (1080P) output. Alarm: 8 in / 1 out. 2 HDD SATA capacity. RJ45 Gigabit. Onvif, P2P, DDNS. 2 USB, 1 RS485. DC48V. Compatible with PoC cameras.
<u>HYU-393</u>	ZVR5216M-POC		16 channel 5 in 1 ZVR HDCVI/HDTV/AHD/CVBS + 2 IP channels. H.265+/H265/H.264+/H264. 2 way audio. 16 channel playback 1080P. Recording 3MP (channels 1 to 4, 15 fps, only TVI), 4MP (2 IP inputs), 1080P (15 fps), 1080N, 720P, 960H, D1/4CIF, VGA, CIF, QVGA, QCIF (25 fps). BNC output at D1/4CIF. HDMI output at 4K and VGA at 1080P. 2 HDD SATA capacity. RJ45 Gigabit. Onvif, P2P, DDNS. 2 USB, 1 RS485. DC48V. Compatible with PoC cameras.
<u>HYU-801</u>	ZVR7216-A-4KLITE-AUDIO		









Analog Recorders HD/CVBS - Analog Recorders with HDD









Reference	Model	Photo	Description
<u>HYU-370-1TB</u>	ZVR5104M-4MLITE-1TB		4 channel 5 in 1 ZVR HDCVI/HDTV/AHD/CVBS + 1 IP channel. H.265+/H265/H.264+/H264. 2 way audio. 4 channel playback at 1080P. Recording: 4M-N, 3MP (channel1, 15 fps, only TVI), 4MP (1 IP input), 1080P (15 fps), 1080N, 720P, 960H, D1/4CIF, VGA, CIF, QVGA, QCIF (25 fps). BNC output at D1/4CIF. HDMI and VGA output at 1080P. Special CCTV HDD of 1 TB. Onvif, P2P, DDNS. 2 USB, 1 RS485. 12V DC.
<u>HYU-373-1TB</u>	ZVR5104M-A-4MLITE-1TB		4 channel 5 in 1 ZVR, HDCVI/HDTV/AHD/CVBS + 1 IP channel. H.265+/H265/H.264+/H264. 2 way audio. 4 channel playback at 1080P. Recording: 4M-N, 3MP (channel 1, 15 fps, only TVI), 4MP (1 IP input), 1080P (15 fps), 1080N, 720P, 960H, D1/4CIF, VGA, CIF, QVGA, QCIF (25 fps). BNC output at D1/4CIF. HDMI and VGA output at 1080P. Alarm: 4 in / 1 out. Special CCTV HDD of 1 TB. Onvif, P2P, DDNS. 2 USB, 1 RS485. 12V DC.









<u>HYU-371-1TB</u>	ZVR5108M-4MLITE-1TB		8 channel 5 in 1 ZVR HDCVI/HDTVI/AHD/CVBS + 2 IP channel. H.265+/H265/H.264+/H264. 2 way audio. 8 channel playback at 1080P. Recording: 4M-N, 3MP (channel1 & 2, 15 fps, only TVI), 4MP (2 IP input), 1080P (15 fps), 1080N, 720P, 960H, D1/4CIF, VGA, CIF, QVGA, QCIF (25 fps). BNC output at D1/4CIF. HDMI and VGA output at 1080P. Special CCTV HDD of 1 TB. Onvif, P2P, DDNS. 2 USB, 1 RS485. 12V DC.
<u>HYU-372-2TB</u>	ZVR5116M-4MLITE-2TB		16 channel 5 in 1 ZVR HDCVI/HDTVI/AHD/CVBS + 2 IP channel. H.265+/H265/H.264+/H264. 2 way audio. 16 channel playback at 1080P. Recording: 4M-N, 3MP (channels 1 to 4, 15 fps, only TVI), 4MP (2 IP inputs), 1080P (15 fps), 1080N, 720P, 960H, D1/4CIF, VGA, CIF, QVGA, QCIF (25 fps). BNC output at D1/4CIF. HDMI output at 4K and VGA at 1080P. Special CCTV HDD of 2 TB. RJ45 Gigabit. Onvif, P2P, DDNS. 2 USB, 1 RS485. 12V DC.









Network Cameras - Mini-Dome





Reference	Model	Photo	Description
<u>HYU-416N</u>	HYU-416N		IP dome with IR illumination of 30m, for outdoors, 2 MP. H.265+, H.265, H.264+, H.264. 1/2,8" CMOS, 2MP. 1080P, 1,3MP, 720P, etc. Mechanical filter. 0,01 lux. 2,8 mm fixed lens (95°). OSD, AGC, BLC, digital WDR, 3D-DNR, motion detection, privacy mask, ROI. IP67, IK10. 3AXIS. 12V DC. PoE.
<u>HYU-770</u>	HYU-770		IP HYUNDAI NEXT GEN IP dome Performance Line with IR of 30m for outdoors, 2 MP. H.265 / H.264 / MJPEG format. 1/2.8" CMOS, 2MP. Digital resolution 1080P @ 25FPS. Mechanical filter. 0.028 lux. 2.8 mm lens (114 °). OSD, AGC, BLC, digital WDR, 3D-DNR, motion detection, privacy masks, fixed ROI zone, IP67, IK10,3AXIS, 12V DC, PoE.
<u>HYU-769</u>	HYU-769		HYUNDAI NEXT GEN IP vandal dome Performance Line with IR of 30m, for outdoors. 2 MP. H.265 / H.264 / MJPEG. 1/2.8" CMOS, 2MP. Digital resolution 1080P @ 25FPS. Mechanical filter. 0.028 lux. 2.8 mm lens (114 °). OSD, AGC, BLC, digital WDR, 3D-DNR, motion detection, privacy masks, fixed ROI zone, IP67, IK10, 2AXIS, 12V DC, PoE.
<u>HYU-749</u>	HYU-749		HYUNDAI IP dome with Smart IR 30 m for outdoor. H.265 / H.264 / MJPEG format. 1/2.8" Sony® Starvis CMOS, 2 MP. 1080P @ 20 fps. Dual Stream 3.6 mm lens. ICR filter OSD, AWB, AGC, digital WDR, 2D / 3D-DNR, 4 ROI zones, motion detection and privacy masks. Audio: 1 in / 1 out. Onvif. IP67 12V DC PoE Reset button
<u>SAM-4598</u>	SAM-4598		AirSpace IP dome with Smart IR 20 m for outdoors. H.265 / H.264 / MJPEG format. 1/2.8" Sony® Starvis CMOS 2 MP. Resolution up to 1080P @ 20 fps. Dual Stream 2.7 ~ 13.5 mm varifocal lens. ICR filter OSD, AWB, AGC, digital WDR, 2D / 3D-DNR, 4 ROI zones, motion detection and privacy masks. Audio: 1 in / 1 out. Onvif. IP67 12V DC PoE Reset button
<u>SAM-4413</u>	IPC-D1B20-L		IP dome Serie ECO-IP with Smart IR of 20 m for indoors. H.265+/H.265/H.264+/H.264/MJPEG. 1/2,7" CMOS, 2MP. Dual Stream. 1080P. 2,8 mm (115°) lens. ICR. 0,09 lux. OSD, AWB, AGC, digital WDR, 3D-DNR, 4 ROI, mirror mode, motion detection and privacy mask. Onvif. 3AXIS. 12V DC. PoE. 100% compatible with DAHUA. SmartPSS, Evo PLUS, IDMSS and DSS

<u>SAM-4600</u>	SAM-4600		IP AirSpace dome with Smart IR 30 m for outdoor. H.265 / H.264 / MJPEG format. 1/2.8" Sony® Starvis CMOS, 2 MP. Resolution up to 1080P @ 20 fps. Dual Stream Motorized optics 2.7 ~ 13.5 mm. ICR filter OSD, AWB, AGC, digital WDR, 2D / 3D-DNR, 4 ROI zones, motion detection and privacy masks. Audio: 1 in / 1 out. Onvif. IP67 12V DC PoE Reset button
<u>SAM-4601</u>	SAM-4601		IP AirSpace dome with Smart IR of 30 m for outdoors. H.265 / H.264 / MJPEG format. 1/2.8" Sony® Starvis CMOS 2 MP. Resolution up to 1080P @ 20 fps. Dual Stream 2.7 ~ 13.5 mm motor lens. ICR filter OSD, AWB, AGC, digital WDR, 2D / 3D-DNR, 4 ROI zones, motion detection and privacy masks. Audio: 1 in / 1 out. Onvif. IP67 12V DC PoE Reset button
<u>HYU-751</u>	HYU-751		HYUNDAI IP fixed dome with 20 m Smart IR for outdoors. H.265 / H.264 format. 1/2.7" CMOS of 5 MP. Resolution of up to 5MP @ 10 fps. Triple Stream 3.6 mm lens. ICR filter OSD, AWB, AGC, digital WDR, 2D / 3D-DNR, 4 ROI zones, motion detection and privacy masks. Audio: 1 input / 1 output. Onvif. IP67 12V DC PoE Reset button
<u>HYU-753</u>	HYU-753		IP dome with IR illumination of 30 meters, for outdoors, 4 MP. H.265+/H.265/H.264/H.264+/MJPEG. 1/3" CMOS, 4MP. Digital resolution 4MP, 1080P, 720P, 20FPS. Mechanical filter. 0,01 lux. 2,8 mm fixed lens (100°). OSD, AGC, BLC, digital WDR, 3D-DNR, motion detection, privacy mask, fixed ROI. IP67. 3AXIS. 12V DC. PoE.
<u>SAM-4605</u>	SAM-4605		AirSpace IP camera with Smart IR of 15 m for outdoors. H.265 / H.264 format. 1/2.7" CMOS, 5 MP. Resolution of up to 5MP @ 10 fps. Triple Stream 2.7 ~ 13.5 mm varifocal lens. ICR filter OSD, AWB, AGC, digital WDR, 2D / 3D-DNR, 4 ROI zones, motion detection and privacy masks. Audio: 1 in / 1 out. Onvif. IP67 12V DC PoE Reset button
<u>HYU-409</u>	HYU-409		IP vandal dome with IR illumination of 30m, for outdoors, 4 MP. H.265+/H.265/H.264/H.264+/MJPEG. 1/3" CMOS, 4MP. Digital resolution: 4MP, 1080P, 720P, 20FPS. Mechanical filter. 0,01 lux. 2,8 mm fixed lens (100°). OSD, AGC, BLC, digital WDR, 3D-DNR, motion detection, privacy mask, fixed ROI. IP67, IK10. 2AXIS. Reset button. 12V DC. PoE.
<u>SAM-4607</u>	SAM-4607		IP AirSpace dome with Smart IR of 30 m for outdoors. H.265 / H.264 format. 1/2.7" CMOS, 5 MP. Resolution of up to 5MP @ 10 fps. Triple Stream. 2.7 ~ 13.5 mm motor lens. ICR filter OSD, AWB, AGC, digital WDR, 2D / 3D-DNR, 4 ROI zones, motion detection and privacy masks. Audio: 1 in / 1 out. Onvif. IP67 12V DC PoE Reset button
<u>SAM-3568</u>	SAM-3568		IP fixed dome with IR illumination of 40 m, for outdoors. H.265/MJPEG. 1/3" CMOS, 4 MP. 4MP @12/15 fps. 2,8 ~ 12 mm autofocus motorized lens. ICR. OSD, WDR, 3D-DNR. 2 way audio. Onvif. IP66. 12V DC. PoE. Waterproof cable. Reset button.

<u>HYU-616</u>	HYU-616		IP dome, 5MP with IR of 30m, suitable for outdoors. H.265+/H.265/H.264+/H.264/MJPEG. 1/2,7" CMOS, 5MP. 5MP@12,5FPS. ICR filter. 0,028 lux. 2,8 mm lens (100°). OSD, AGC, BLC, Real WDR 120dB, 3D-DNR, motion detection, privacy mask, 1 fixed ROI. Onvif, ISAPI. IP67. 2AXIS. 12V DC. PoE.
<u>HYU-772</u>	HYU-772		IP HYUNDAI NEXT GEN vandal dome Performance Line with IR of 30m, for outdoors. 2 MP. H.265 + / H.265 / H.264 + / H.264 / MJPEG format. 1/2.8" CMOS, 2MP. Digital resolution 1080P @ 25FPS. Mechanical filter. 0.028 lux. 2.8 ~ 12 mm motor lens (99.6 ° ~ 35 °). OSD, AGC, BLC, WDR 120dB , 3D-DNR, motion detection, privacy masks, fixed ROI zone Intelligent analysis IP67, IK10, 3AXIS, 12V DC, PoE.
<u>HYU-773</u>	HYU-773		IP HYUNDAI NEXT GEN dome Performance Line with IR of 30m, for outdoor. 4 MP. H.265 + / H.265 / H.264 + / H.264 / MJPEG format. 1/3 " CMOS, 4MP. Digital resolution of 4MP @ 20FPS. Mechanical filter. 0.02 lux. 2.8 ~ 12 mm motor lens (92.8 ° ~ 29 °). OSD, AGC, BLC, WDR 120dB , 3D-DNR, motion detection, privacy masks, fixed ROI zone, IP67,IK10 3AXIS, 12V DC, PoE.
<u>HYU-418</u>	HYU-418		IP dome with IR of 20~30m, for outdoors of 2 MP. H.265+/H.265/H.264+/H.264/MJPEG. 1/2,8" CMOS, 2MP. Digital resolution: 1080P, 1,3MP, 720P, etc. Mechanical filter. 0,01 lux. 2,8~12 mm (90°~35°) motor lens with autofocus. OSD, AGC, BLC, digital WDR, 3D-DNR, motion detection, privacy mask, fixed ROI. IP67. 3AXIS. 12V DC. PoE.
<u>HYU-742</u>	HYU-742		HYUNDAI NEXTGEN IP dome of 4MP with IR of 30m, vandal proof suitable for outdoors. H.265 + / H.265 / H.264 + / H.264 / MJPEG format. Triple stream. CMOS 1/3 "of 4MP. Digital resolution of 4MP @ 25 fps. ICR filter. 0.018 lux. Fixed optics of 2.8 mm (103 °). OSD, AGC, BLC, HLC, real WDR 120dB, 3D-DNR, 1 fixed ROI zone IVS Facial detection Reset button MicroSD Onvif, ISAPI IP67, IK10 3AXIS 12V DC PoE.
<u>HYU-413</u>	HYU-413		IP vandal dome with IR of 30m, for outdoors, 4 MP. H.265+/H.265/H.264/H.264+/MJPEG. 1/3" CMOS, 4MP. Digital resolution 4MP, 1080P, 720P, 20FPS. Mechanical filter. 0,01 lux. 2,8~12 mm (98°~30°) motor lens with autofocus. OSD, AGC, BLC, real WDR 120dB, 3D-DNR, motion detection, privacy mask, fixed ROI. MicroSD/SDHC/SDXC. IP67, IK10. 3AXIS. 12V DC. PoE.
<u>HYU-767</u>	HYU-767		HYUNDAI IP dome with IR of 30m , 4MP for outdoors. H.265 / H.264 / MJPEG format. 1/3" CMOS, 4MP. Digital resolution of 4MP, 1080P, 720P, 20FPS. Mechanical filter. 0.018 lux. 2.8 ~ 12 mm (98 ° ~ 28 °) motor lens with autofocus. OSD, AGC, BLC, WDR true 120dB, 3D-DNR, motion detection, privacy masks, fixed ROI zone, MicroSD / SDHC / SDXC slot, IP67, IK10, 3AXIS, 12V DC, PoE.
<u>HYU-766</u>	HYU-766		IP dome with IR illumination of 20~30m, for outdoors 4 MP. H.265+/H.265/H.264/H.264+/MJPEG. 1/3" CMOS, 4MP. Digital resolution 4MP, 1080P, 720P, 20FPS. Mechanical filter. 0,01 lux. 2,8~12 mm (98°~30°) motorized lens with autofocus. OSD, AGC, BLC, real WDR 120dB, 3D-DNR, motion detection, privacy mask, fixed ROI. IP67. 3AXIS. 12V DC. PoE.









<u>HYU-412N</u>	HYU-412N		IP dome with IR illumination of 20~30m, for outdoors 4 MP. H.265+/H.265/H.264/H.264+/MJPEG. 1/3" CMOS, 4MP. Digital resolution 4MP, 1080P, 720P, 20FPS. Mechanical filter. 0,01 lux. 2,8~12 mm (98°~30°) motorized lens with autofocus. OSD, AGC, BLC, real WDR 120dB, 3D-DNR, motion detection, privacy mask, fixed ROI. IP67, IK10. 3AXIS. 12V DC. PoE.
<u>HYU-494</u>	HYU-494		IP dome with IR of 30m, for outdoors 6 MP. H.265+/H.265/H.264/H.264+/MJPEG. 1/2,9" CMOS, 6MP. Digital resolution: 6MP, 5MP, 4MP, 1080P, 720P, 20FPS. Mechanical filter. 0,01 lux. 2,8 mm (97°) fixed lens. OSD, AGC, BLC, real WDR 120dB, 3D-DNR, motion detection, privacy mask, fixed ROI. Intelligent functions. Facial detection. MicroSD/SDHC/SDXC. IP67. 3AXIS. 12V DC. PoE.
<u>HYU-493</u>	HYU-493		IP vandal dome Performance Line with IR of 30m, for outdoors 6 MP. H.265+/H.265/H.264/H.264+/MJPEG. 1/2,9" CMOS, 6MP. Digital resolution: 6MP, 5MP, 4MP, 1080P, 720P, 20FPS. Mechanical filter. 0,01 lux. 2,8 mm (97°) fixed lens. OSD, AGC, BLC, real WDR 120dB, 3D-DNR, motion detection, privacy mask, fixed ROI. Intelligent functions. Facial detection. MicroSD/SDHC/SDXC. IP67, IK10. 3AXIS. 12V DC. PoE
<u>HYU-610</u>	HYU-610		2MP IP AIsense IP dome with IR illumination of 50m, suitable for outdoors. H.265/H.264/MJPEG. 1/2,8" CMOS, 2MP. 2MP@25 fps. ICR. 0,012 lux. 2,8 mm lens (108°). OSD, AGC, BLC, real WDR 120dB, 3D-DNR, 1 fixed ROI. IVS. Reset button. MicroSD. Onvif, ISAPI. IP67. 3AXIS. 12V DC. PoE
<u>HYU-614</u>	HYU-614		2MP IP AIsense dome with IR of 30m, vandal protection suitable for outdoors. H.265/H.264/MJPEG. 1/2,8" CMOS, 2MP. 2MP@25 fps. ICR. 0,009 lux. 2,8 mm lens (108°). OSD, AGC, BLC, real WDR 120dB, 3D-DNR, 1 fixed ROI. IVS. Reset button. MicroSD. Onvif, ISAPI. IP67, IK10. 3AXIS. 12V DC. PoE.
<u>HYU-609</u>	HYU-609		4MP AIsense IP dome with IR illumination of 50m, suitable for outdoors. H.265/H.264/MJPEG. 1/2,7" CMOS, 4MP. 4MP@25 fps digital resolution. ICR. 0,012 lux. 2,8 mm lens (104°). OSD, AGC, BLC, real WDR 120dB, 3D-DNR, 1 fixed ROI. IVS. Reset button. MicroSD. Onvif, ISAPI. IP67. 3AXIS. 12V DC. PoE.
<u>SAM-4367</u>	SAM-4367		IP vandal dome PRO series with Smart IR of 50 m, for outdoors. 1/2,9" CMOS, 6 MP. H.265 / H.264 / MJPEG. Triple stream. 6MP resolution. 2,7 ~ 13,5 mm motor lens (H: 104,2°~27,7°, V: 72,1°~20,1°). 0,002/0,0002 lux. ICR filter. OSD, AWB, AGC, real WDR 120dB, 3D-DNR, ROI, Defog, motion detection and privacy mask, mirror mode. IVS. MicroSD slot. Onvif. IP67, IK10. 3AXIS. 12V DC. PoE.
<u>HYU-285</u>	HYU-285		IP fixed dome with IR illumination of 40m, for outdoors. 8 MP. H.265/H.264/MJPEG. 1/2,5" CMOS, 8MP. Triple stream. Mechanical filter. 0,01 lux. 2,8 mm fixed lens (102°). OSD, 3D-NR, BLC, real WDR 120dB, privacy mask, 1 ROI zone. IVS. MicroSD//SDHC/SDXC slot. IP67. 3AXIS. 12V DC. PoE.







<u>HYU-677</u>	HYU-677		IP minidome Color View series, 2MP with white illumination up to 30m, suitable for outdoors. H.265+/ H.265/ H.264+/ H.264/ MJPEG. 1/2,8" CMOS, 2MP. 1080P@25 fps. 0,0035 lux F1.0. 4 mm lens (89°). OSD, AGC, BLC, WDR true 120dB, 3D-DNR, 1 fixed ROI. IVS. Reset button. MicroSD. Onvif, ISAPI. IP67. 3AXIS. 12V DC. PoE.
<u>HYU-426</u>	HYU-426		IP dome with IR illumination of 30m, vandal protection for outdoors. H.265/H.264/MJPEG. 1/2,5" CMOS, 8MP. Triple Stream. Digital resolution of 8MP@12,5fps. ICR filter. 0,028 lux. 2,8 mm lens (102°). OSD, BLC, HLC, WDR 120dB, 3D-DNR, privacy mask, 1 ROI, image adjustment. IVS. Facial detection. MicroSD//SDHC/SDXC slot. IP67, IK10. 3AXIS. 12V DC. PoE.
<u>HYU-620</u>	HYU-620		IP dome, 5MP with IR of 30m, for outdoors. H.265+/H.265/H.264+/H.264/MJPEG. 1/2,7" CMOS, 5MP. 5MP@12,5FPS. ICR. 0,02 lux. 2,8 ~12 mm motor lens (98°~28°). OSD, AGC, BLC, real WDR 120dB, 3D-DNR, motion detection and privacy mask, 1 fixed ROI. Reset button. MicroSD. Onvif, ISAPI. IP67. 3AXIS. 12V DC. PoE.
<u>HYU-619</u>	HYU-619		IP dome, 5MP with IR of 30m, vandal protection for outdoors. H.265+/H.265/H.264+/H.264/MJPEG. 1/2,7" CMOS, 5MP. 5MP@12,5FPS. ICR filter. 0,02 lux. 2,8 ~12 mm motor lens (98°~28°). OSD, AGC, BLC, real WDR 120dB, 3D-DNR, motion detection, privacy mask, 1 fixed ROI. Reset button. MicroSD. Onvif, ISAPI. IP67, IK10. 3AXIS. 12V DC. PoE.
<u>HYU-394</u>	HYU-394		WiFi vandal IP dome with IR of 10 m, for outdoors, 4MP. H.264/H.264+/MJPEG. 1/3" CMOS, 4MP. Dual Stream. MEchanical filter. 0,01 lux. 2,8 mm fixed lens (106°). OSD, 3D-NR, BLC, real WDR 120dB, ROI. IVS. MicroSD//SDHC/SDXC. IP67, IK08. 12V DC. PoE.
<u>HYU-498</u>	HYU-498		WiFi IP dome Performance Line with IR of 10m, for outdoors, 6 MP. H.265+/H.265/H.264/H.264+/MJPEG. 1/2,9" CMOS, 6MP. Digital resolution: 6MP, 5MP, 4MP, 1080P, 720P, 20FPS. Mechanical filter. 0,01 lux. 2,8 mm (80°) fixed lens. OSD, AGC, BLC, real WDR 120dB, 3D-DNR, motion detection, privacy mask, ROI fixed zone. Intelligent functions. Facial detection. MicroSD/SDHC/SDXC slot. IP67, IK08. 3AXIS. 12V DC. PoE.
<u>HYU-676</u>	HYU-676		IP minidome Color View series de 4MP with white illumination up to 20m, for outdoors. H.265+/ H.265/ H.264+/ H.264/ MJPEG. 1/1,8" CMOS, 4MP. 4MP@25 fps. 0,0014 lux F1.0. 4 mm lens (94°). OSD, AGC, BLC, WDR true 120dB, 3D-DNR, 1 ROI. IVS. Reset button. MicroSD. Onvif, ISAPI. IP67. 3AXIS. 12V DC. PoE.
<u>SAM-4013</u>	SAM-4013		IP fixed dome with IR of 40 m for outdoors. H.265/MJPEG. 1/2,5" Sony® Starvis CMOS, 8 MP. 8MP @25/30 fps. Dual stream. 3,6 ~ 12 mm autofocus motorized lens. ICR. OSD, WDR, 3D-DNR, motion detection and privacy mask. Audio: 1 in/ 1 out. Onvif. IP66. 12V DC IN/OUT (to power the microphone). PoE. Reset button. Waterproof cable. 3AXIS.

<u>HYU-744</u>	HYU-744		HYUNDAI NEXTGEN IP dome of 4MP with IR of 30m, vandal-proof suitable for outdoors. H.265 + / H.265 / H.264 + / H.264 / MJPEG format. Triple stream. 1/3" CMOS of 4MP. Digital resolution of 4MP @ 25 fps. ICR filter. 0.018 lux. 2.8 ~ 12 mm motor lens with autofocus (104 ° ~ 29 °). OSD, AGC, BLC, HLC, WDR true 120dB, 3D-DNR, 1 fixed ROI zone IVS Face detection. Two-way audio. Alarm: 1 in / 1 out BNC video output
<u>HYU-500</u>	HYU-500		IP-vandal dome Performance Line with IR of 30m, for outdoors, 6 MP. H.265+/H.265/H.264/H.264+/MJPEG. 1/2,9" CMOS, 6MP. Digital resolution: 6MP, 5MP, 4MP, 1080P, 720P, 20FPS. Mechanical filter. 0,01 lux. 2,8~12 mm (88°~27°) motorized lens with autofocus. OSD, AGC, BLC, real WDR 120dB, 3D-DNR, motion detection, privacy mask, fixed ROI. Intelligent functions. 2 way audio. Alarm: 1 in / 1 out. MicroSD/SDHC/SDXC. IP67, IK10. 3AXIS. 12V DC. PoE.
<u>HYU-665</u>	HYU-665		Alsense IP dome of 2MP with IR illumination of 30 m, for outdoors. H.265+/H.265/H.264+/H.264/MJPEG. 1/2,8" CMOS, 2MP. 1080P@25 fps. ICR. 0,007 lux. 2,8~12 mm motor lens (113°~32°) with autofocus. OSD, AGC, BLC, WDR true 120dB, 3D-DNR, 1 fixed ROI. IVS. 2 way audio. Alarm: 1 in / 1 out. Reset button. MicroSD. Onvif, ISAPI. IP67, IK10. 3AXIS. 12V DC. PoE.
<u>HYU-667</u>	HYU-667		Alsense IP dome of 4MP with IR of 30m, for outdoors. H.265+/H.265/H.264+/H.264/MJPEG. 1/2,7" CMOS, 4MP. 4MP@25 fps. ICR. 0,01 lux. 2,8~12 mm (101°~29°) motor lens with autofocus. OSD, AGC, BLC, WDR true 120dB, 3D-DNR, 1 fixed ROI . IVS. 2 way audio. Alarm: 1 in / 1 out. Reset button. MicroSD. Onvif, ISAPI. IP67, IK10. 3AXIS. 12V DC. PoE.

Network Cameras - Bullet

Reference	Model	Photo	Description
<u>SAM-4595</u>	SAM-4595		AirSpace IP bullet camera with 20 m Smart IR for outdoor. H.265 / H.264 / MJPEG format. 1/2.8" Sony® Starvis CMOS, 2 MP. Resolution up to 1080P @ 20 fps. Dual Stream 2.8 mm fixed lens. ICR filter OSD, AWB, AGC, digital WDR, 2D / 3D-DNR, 4 ROI zones, motion detection and privacy masks. Audio: 1 in / 1 out. Onvif. IP67 12V DC PoE Reset button
<u>HYU-768</u>	HYU-768		HYUNDAI NEXT GEN IP bullet camera Performance Line with IR of 30m, 2 MP. H.265 / H.264 / MJPEG format. 1/2.8" CMOS, 2MP. Digital resolution of 1080P@25FPS. Mechanical filter. 0.028 lux. 2.8 mm lens (114.8 °). OSD, AGC, BLC, digital WDR, 3D-DNR, motion detection, privacy masks, fixed ROI zone, IP67, 3AXIS, 12V DC, PoE.
<u>SAM-4398</u>	IPC-B1B20-L		IP bullet camera Serie ECO-IP with Smart IR of 30 m, for outdoors. H.265+/H.265/H.264+/H.264/MJPEG. 1/2,7" CMOS, 2MP. Dual stream. 1080P. 2,8 mm (115°) lens. ICR. 0,09 lux. OSD, AWB, AGC, digital WDR, 3D-DNR, 4 ROI, mirror mode, motion detection and privacy mask. Onvif. IP67. 3AXIS. 12V DC. PoE. 100% compatible with DAHUA. SmartPSS, Evo PLUS, IDMSS and DSS.
<u>SAM-4602</u>	SAM-4602		AirSpace IP bullet camera with 20 m Smart IR for outdoor. H.265 / H.264 format. 1/2.7" CMOS, 5 MP. Resolution of up to 5MP @ 10 ips. Triple Stream 2.8 mm lens. ICR filter OSD, AWB, AGC, digital WDR, 2D / 3D-DNR, 4 ROI zones, motion detection and privacy masks. Audio: 1 in / 1 out. Onvif. IP67 12V DC PoE Reset button.

<u>SAM-4401</u>	IPC-B1B40		IP bullet camera Serie ECO-IP with Smart IR of 30 m for outdoors. H.265+/H.265/H.264+/H.264/MJPEG. 1/3" CMOS 4MP. Dual stream. 4MP.@20FPS. 2,8 mm (101°) lens. ICR. 0,09 lux. OSD, AWB, AGC, digital WDR, 3D-DNR, 4x ROI, mirror mode, motion detection and privacy mask. Onvif. IP67. 3AXIS. 12V DC. PoE. 100% compatible with DAHUA. SmartPSS, Evo PLUS, IDMSS and DSS
<u>HYU-752</u>	HYU-752		IP bullet camera with IR illumination of 30m, for outdoors, 4 MP. Formato H.265+/H.265/H.264/H.264+/MJPEG. 1/3" CMOS, 4MP. Digital resolution: 4MP, 1080P, 720P, 20FPS. Mechanical filter. 0,01 lux. 2,8 mm fixed lens (100°). OSD, AGC, BLC, digital WDR, 3D-DNR, motion detection, privacy mask, fixed ROI. IP67. 3AXIS bracket. 12V DC. PoE.
<u>SAM-4604</u>	SAM-4604		AirSpace IP bullet camera with Smart IR of 40 m for outdoors. H.265 / H.264 format. 1/2.7" CMOS, 5 MP. Resolution of up to 5MP @ 10 fps. Triple Stream 2.7 ~ 13.5 mm motor lens. ICR filter OSD, AWB, AGC, digital WDR, 2D / 3D-DNR, 4 ROI zones, motion detection and privacy masks. Audio: 1 in / 1 out. Onvif. IP67 12V DC PoE Reset button
<u>HYU-307</u>	HYU-307		IP bullet camera with IR illumination of 40 m, for outdoors. H.265/H.264. 1/3" CMOS, 4 MP. 4MP @15 fps. Dual Stream. 2,8 ~ 12 mm autofocus motorized lens. ICR filter. OSD, WDR, 2 way audio, 3D-DNR, motion detection and privacy mask. Onvif. IP66. 12V DC. PoE. Reset button. Waterproof cable.
<u>HYU-771</u>	HYU-771		HYUNDAI NEXT GEN Performance Line IP vandal bullet camera with IR of 30m, 2 MP for outdoors. H.265 / H.264 / MJPEG format. 1/2.8" CMOS, 2MP. Digital resolution 1080P @ 25FPS. Mechanical filter. 0.028 lux. 2.8 ~ 12 mm motor lens (99.6 ° ~ 35 °). OSD, AGC, BLC, WDR 120dB , 3D-DNR, motion detection, privacy masks, fixed ROI zone, intelligent analysis, IP67, 3AXIS, 12V DC, PoE.
<u>HYU-411</u>	HYU-411		IP bullet camera with IR illumination of 30 m, for outdoors, 4 MP. H.265+/H.265/H.264/H.264+/MJPEG. 1/3" CMOS, 4MP. 4MP, 1080P, 720P, 20FPS. Mechanical filter. 0,01 lux. 2,8~12 mm motor lens (98°~28°) with autofocus. OSD, AGC, BLC, real WDR 120dB, 3D-DNR, motion detection, privacy mask, fixed ROI. SD slot. IP67. 3AXIS bracket. Reset button. 12V DC. PoE.
<u>HYU-760</u>	HYU-760		IP bullet camera with IR illumination of 30 m, for outdoors, 4 MP. H.265+/H.265/H.264/H.264+/MJPEG. 1/3" CMOS, 4MP. 4MP, 1080P, 720P, 20FPS. Mechanical filter. 0,01 lux. 2,8~12 mm motor lens (98°~28°) with autofocus. OSD, AGC, BLC, real WDR 120dB, 3D-DNR, motion detection, privacy mask, fixed ROI. SD slot. IP67. 3AXIS bracket. Reset button. 12V DC. PoE.
<u>HYU-612</u>	HYU-612		2 MP Alsense IP bullet camera with IR illumination 50m, suitable for outdoors. H.265/H.264/MJPEG. 1/2,8" CMOS, 2MP. 2MP@25 fps. ICR. 0,009 lux. 2,8 mm lens (104°). OSD, AGC, BLC, real WDR 120dB, 3D-DNR, 1 fixed ROI. IVS. Reset button. MicroSD. Onvif, ISAPI. IP67. 3AXIS. 12V DC. PoE+.


<u>HYU-679</u>	HYU-679		IP bullet camera Color View series with 2MP with white illumination up to 30m, for outdoors. H.265+/ H.265/ H.264+/ H.264/ MJPEG. 1/2,8" CMOS, 2MP. Digital resolution of 1080P@25 fps. 0,0035 lux F1.0. 4 mm lens (89°). OSD, AGC, BLC, WDR true 120dB, 3D-DNR, 1 fixed ROI. IVS. Reset button. MicroSD. Onvif, ISAPI. IP67. 3AXIS. 12V DC. PoE.
<u>HYU-203</u>	HYU-203		IP bullet camera with IR illumination of 30 meters, for outdoors. 4MP. H.264/H.264+/MJPEG. 1/3" CMOS, 4MP. 4MP /1080P /720P /CIF. mechanical filter. 0,014 lux. 2,8~12 mm motorized lens (112°~33,8°). OSD, 3D-NR, BLC, real WDR (120 dB), privacy mask, ROI. Intelligent functions (IVS). MicroSD//SDHC/SDXC. IP67. 12V DC. PoE.
<u>HYU-678</u>	HYU-678		IP bullet camera Color View series of 4MP with white illumination up to 30m, for outdoors. H.265+/ H.265/ H.264+/ H.264/ MJPEG. 1/1,8" CMOS, 4MP. 4MP@25 fps. 0,0014 lux F1.0. 4 mm lens (94°). OSD, AGC, BLC, WDR true 120dB, 3D-DNR, 1 fixed ROI. IVS. Reset button. MicroSD. Onvif, ISAPI. IP67. 3AXIS. 12V DC. PoE.
<u>HYU-740</u>	HYU-740		4MP HYUNDAI NEXTGEN IP bullet camera with 50m infrared illumination, vandal proof for outdoor use. H.265 + / H.265 / H.264 + / H.264 / MJPEG format. Triple stream. CMOS 1/3 "of 4MP. Digital resolution of 4MP @ 25 fps. ICR filter. 0.018 lux. Motorized optics 2.8 ~ 12 mm with autofocus (104 ° ~ 29 °). OSD, AGC, BLC, HLC, WDR real 120dB, 3D-DNR, 1 fixed ROI zone IVS Face detection Two-way audio 1 input / 1 alarm output PNG video output Reset button MicroSD Onvif ISAPI IP67 IK10
<u>HYU-666</u>	HYU-666		Alsense IP bullet camera of 2MP with IR of 50m, for outdoors. H.265+/H.265/H.264+/H.264/MJPEG. 1/2,8" CMOS, 2MP. 1080P@25 fps. ICR filter. 0,007 lux. 2,8~12 mm (113°~32°) motor lens with autofocus. OSD, AGC, BLC, WDR true 120dB, 3D-DNR, 1 fixed ROI. IVS. 2 way audio. Alarm: 1 in / 1 out. Reset button. MicroSD. Onvif, ISAPI. IP67, IK10. 3AXIS. 12V DC. PoE+.
<u>HYU-668</u>	HYU-668		IP Alsense bullet camera of 4MP with IR 50m, for outdoors. H.265+/H.265/H.264+/H.264/MJPEG. 1/2,7" CMOS, 4MP. 4MP@25 fps. ICR. 0,01 lux. 2,8~12 mm motor lens (101°~29°) with autofocus. OSD, AGC, BLC, WDR true 120dB, 3D-DNR, 1 fixed ROI. IVS. 2 way audio. Alarm: 1 in / 1 out. Reset button. MicroSD. Onvif, ISAPI. IP67, IK10. 3AXIS. 12V DC. PoE+.

Network Cameras - PTZ Dome


Reference	Model	Photo	Description
<u>HYU-237</u>	HYU-237		IP motorized dome of 60°/sec with IR illumination of 20 meters, for indoors. H.264/MJPEG. 1/3" CMOS, 2MP. Dual stream. 2X optical zoom of 3.6~8.6 mm (77°~50°). 16X digital zoom. ICR. OSD, AWB, AGC, BLC, digital WDR, 3D-NR, motion detection, privacy mask, 4 ROI zones. Intelligent detection (IVS). 300 presets. Audio: 1in/1out. Alarm: 1in/ 1out. MicroSD/SDHC/SDXC. Onvif, PSIA, CG, P2P. IP54, Lightning-proof. 12V DC. PoE.
<u>HYU-428N</u>	HYU-428N		IP PTZ of 80°/sec. with Smart IR of 100 m, for outdoors. H.265+/H.265/H.264+/H.264/MJPEG. 1/2,8" CMOS, 2 MP. Triple stream. Resolution up to 2MP. 25X optical zoom of 4,8~120 mm. 16X digital zoom. ICR. OSD, AWB, AGC, BLC, real WDR 120 dB, 3D-NR, motion detection, privacy mask, defog, 4 ROI. IVS. 300 presets. MicroSD/SDHC/SDXC. Onvif, PSIA, CGI. IP66, Lightning-proof. 12V DC. PoE+ supported. Bracket and power supply is included.

<u>HYU-688</u>	HYU-688		IP PTZ of 80°/sec. with Smart IR of 100 m, for outdoors. H.265+/H.265/H.264+/H.264/MJPEG. 1/2,5" CMOS 4 MP. Triple stream. 4MP. 15X optical zoom of 5~75 mm. 16X digital zoom. ICR filter. OSD, AWB, AGC, BLC, WDR true 120 dB, 3D-NR, motion detection, privacy mask, defog. IVS. 300 presets. MicroSD/SDHC/SDXC. Onvif, ISAPI, SDK. IP66, Lightning-proof. 12V DC. PoE+ supported. Bracket and power supply included.
<u>HYU-687</u>	HYU-687		IP PTZ of 80°/sec. with Smart IR of 100 m, for outdoors. H.265+/H.265/H.264+/H.264/MJPEG. 1/2,5" CMOS, 4 MP. Triple Stream. 4MP. 25X optical zoom of 4,8~120 mm. 16X digital zoom. ICR. OSD, AWB, AGC, BLC, WDR true 120 dB, 3D-NR, motion detection, privacy mask, defog. IVS. 300 presets. MicroSD/SDHC/SDXC. Onvif, ISAPI, SDK. IP66, Lightning-proof. 12V DC. PoE+ supported. Wall mount and power supply included.
<u>HYU-386</u>	HYU-386		IP motorized dome straight of 120°/sec. with Smart IR of 150 m, for outdoors. H.265+/H.265/H.264+/H.264/MJPEG. 1/2,8" CMOS, 2 MP. Triple Stream. 2MP resolution. 25X optical zoom of 4,8~120 mm (57,6°~2,5°). 16X digital zoom. ICR filter. OSD, AWB, ATW, AGC, BLC, HLC, real WDR 120 dB, 3D-DNR, EIS, motion detection, privacy mask, defog, 4 ROI per stream. IVS. 300 presets. MicroSD/SDHC/SDXC slot. Onvif, PSIA, CGI. IP66, Lightning-proof. 24V AC. Hi-PoE supported. Bracket and power supply included.
<u>HYU-455</u>	HYU-455		IP PTZ dome, 350°/s with IR of 150 m for outdoors. 1/2,8" Sony CMOS, 2 MP. 40X optical zoom. ICR filter. OSD, AWB, AGC, BLC, 3D-NR, WDR, mirror mode. 256 presets. 2 way audio. Alarm: 1 in / 1 out. Onvif. IP66, Lightning-proof. 12V DC.
<u>HYU-690</u>	HYU-690		IP PTZ of 160°/sec. with Smart IR of 150 m, for outdoors. H.265+/H.265/H.264+/H.264/MJPEG. 1/2,8" CMOS, 2 MP. Triple Stream. 1080P. 32X optical zoom 4,8~153 mm. 16X digital zoom. ICR filter. OSD, AWB, AGC, BLC, WDR true 120 dB, 3D-NR, motion detection, privacy mask, defog. IVS. 300 presets. MicroSD/SDHC/SDXC. Onvif, ISAPI, CGI. IP66, Lightning-proof. 24V AC. Hi-PoE supported. Bracket and power supply is not included.

Network Cameras - Positioning Systems

Reference	Model	Photo	Description
<u>HYU-259</u>	HYU-259		PTZ bullet IP camera with IR illumination of 100 m for outdoors. 1/2,8 CMOS, 3 MP. H.264/H.265/MJPEG/JPEG. 3MP resolution. 20X optical zoom. ICR filter. OSD, AWB, AGC, BLC, real WDR, 3D-NR. 360° positioner. 256 presets. IP66, Lightning-proof. 12V DC


Network Cameras - Fisheye & Panoramic Cameras

Reference	Model	Photo	Description
<u>HYU-484</u>	HYU-484		Indoor IP PTZ (30°/sec.) with 3 fixed cameras and 1 motorized. IR of Ø20 m. H.265/H.264/MJPEG. 1/2,8" CMOS, 2 MP. 2MP. 3x 2 mm fixed cameras(128,5°) + 1 motorized camera with optical zoom 4X de 2,8~12 mm (120°~56,6°). Filtro ICR. 0,05/0,01 lux. OSD, AWB, AGC, BLC, HLC, digital WDR, 3D-DNR, 8 ROI, motion detection, privacy mask, defog. 300 presets. MicroSD/SDHC/SDXC. Onvif, ISAPI, CGI. Lightning-proof. 24V AC. 12V DC. PoE+ supported. Bracket and power supply included.





Network Cameras - Hidden & Mini Cameras

Reference	Model	Photo	Description
<u>HYU-401</u>	HYU-401		Day/night IP camera. H.264/MJPEG. 1/4" CMOS, 1MP. 720P @30 fps. 2,8 mm fixed lens. Electronic filter. 0,028 lux. OSD, AGC, BLC, digital WDR, 3D-DNR, motion detection and privacy mask. IVS. Onvif. 12V DC.
<u>HYU-495</u>	HYU-495		WiFi IP compact camera Performance Line with IR illumination of 10m, for indoors, 6 MP. H.265+/H.265/H.264/H.264+/MJPEG. 1/2,8" CMOS, 6MP. Digital resolution: 6MP, 5MP, 4MP, 1080P, 720P, 20FPS. Mechanical filter. 0,01 lux. 2,8 mm (80°) fixed lens. OSD, AGC, BLC, real WDR 120dB, 3D-DNR, motion detection, privacy mask, fixed ROI. Intelligent functions. Facial detection. 2 way audio. MicroSD/SDHC/SDXC. 12V DC. PoE

Network Cameras - People Counting

Reference	Model	Photo	Description
<u>HYU-519</u>	HYU-519		IP smart camera for people counting. H.264. Dual stream. 1/3" CMOS. 640x960 resolution. 2 mm lens (100°) and 2,8 mm lens (82°). 3D-DNR, 1 ROI per stream, Brightness adjustments. Alarm: 1 in / 1 out. 12V DC. PoE.

Network Recorders - Network Recorders



Reference	Model	Photo	Description
<u>HYU-525</u>	NVR3104P		4 channels IP NVR. H.265+/H.265/H.264+/H.264. 1 channel 4MP or 2 channel 1080P. Display up to 4MP. Recording: 4MP, 3MP, 1080P, UXGA, 720P, 4CIF, etc. 40 Mbps. VGA and HDMI output at 1080P.1 HDD SATA. 2 USB. Compatible with Onvif, P2P, DDNS. 12V DC. Desktop.
<u>HYU-280N</u>	NVR4104M-4P-4K		4 channel IP NVR. H.265/H.264/MPEG4. Up to 4 channel 1080P. 8MP display. 8MP, 6MP, 5MP, 4MP, 3MP, 1080P, 720P, 4CIF, etc. Recording up to 40 Mbps. VGA at 1080P and HDMI at 4K output. 2 way audio. 1 HDD SATA supported. Onvif, P2P, DDNS. 48V CC. Desktop. 4 PoE+ ports.
<u>HYU-754</u>	NVR3116M-16P-4K		16 ch HYUNDAI NEXTGEN IP NVR. H.265/H.265+/H.264/H.264+/MPEG4. Synchronous playback of 16 channels. Display up to 8MP. Recording 8MP, 6MP, 5MP, 4MP, 3MP, 1080P, UXGA, 720P, 4CIF, etc. Recording up to 160 Mbps. HDMI 4K and VGA 1080P output. 2 way audio. Supports 1 SATA HDD. RJ45 Gigabit Compatible Onvif, P2P, DDNS. 12V DC 16 PoE +.
<u>HYU-634</u>	NVR7208-8P-AI		8 channel Aisense IP NVR. H.265+/H.265+/H.264/H.264+/MPEG4. playback up to 8 ch at 1080p. 8MP display. Recording: 12MP, 8MP, 6MP, 5MP, 4MP, 3MP, 1080P, UXGA, 720P, 4CIF, etc. Recording up to 80 Mbps. VGA at 1080P and HDMI at 4K. BNC video output. 2 way audio. Alarm: 4 in / 1 out. 2 HDD SATA supported. RJ45 Gigabit. POS function. IVS: 4 ch of false alarm filters. Compatible with Onvif, P2P, DDNS. 220V AC. 8 PoE+ ports.

HYU-654	NVR7216-16P-AI		16 channel Aisense IP NVR. H.265/H.265+/H.264/H.264+/MPEG4. playback up to 12 ch at 1080p. 8MP display. Recording: 12MP, 8MP, 6MP, 5MP, 4MP, 3MP, 1080P, UXGA, 720P, 4CIF, etc. Recording up to 160 Mbps. VGA at 1080P and HDMI at 4K. BNC video output. 2 way audio. Alarm: 4 in / 1 out. 2 HDD SATA supported. RJ45 Gigabit. POS function. IVS: 4 ch of false alarm filters. Compatible with
-------------------------	----------------	---	--


Control Center & Keyboards - Keyboard & Joystick

Reference	Model	Photo	Description
HYU-354	HYU-354		4AXIS IP keyboard for DVR/DVS, NVR, matrix, cameras and IP dome, etc. Up to 1000 devices. 128x64 LCD screen. 12V DC.
HYU-579	HYU-579		IP WiFi 4AXIS keyboard for control of DVR/DVS, NVR, matrix, IP domes and cameras, etc. DVI/HDMI output. Display up to 16 channels. Up to 200 device management. LCD screen 1024x600. 12V DC.

Network Communications - Professional Wireless




Reference	Model	Photo	Description
SAM-4624	UC-CK		Cloud Key controller to manage 50 UniFi devices from the cloud, hotspot server, email alerts, mass updates, etc. 802.3af
SAM-4530	UAP-AC-M-PRO		Wireless access point (802.11a/b/g/n/ac) for outdoors. Dual MiMo 3x3 band up to 1750Mbps. 22dBm. 3 omnidirectional antennas of 8 dBi. 2x RJ45 puerto Ethernet. PoE 48V included. Reset button.

Network Communications - SOHO Wireless





Reference	Model	Photo	Description
SAM-4386	UAP-AC-IW		Dual frequency wireless antenna (2,4GHz @802.11n / 5GHz @802.11ac) for access point (connected to switch with router). 55~100Mbps @2,4GHz and 150~200Mbps @5GHz. 30 m range open field. 2 dBi gain antenna (MIMO 2x2). 180° aperture. 3x RJ45 Ethernet. Power supply is not included

Network Communications - Commercial Switches


Reference	Model	Photo	Description
-----------	-------	-------	-------------

<u>HYU-821</u>	HYU-821		
<u>SAM-4139</u>	SAM-4139		8 port switch PoE 10/100M + 2 RJ45 uplink ports of 100M. 30W per port with a total of 96W. CCTV mode with transmission up to 250 meters. 48V DC.
<u>HYU-822</u>	HYU-822		
<u>SAM-4134</u>	SAM-4134		16x 10/100M switch PoE port. 30W per port (150W total). CCTV mode with 250 meter transmission.. 220V AC.

Network Communications - Accesories / Power Supplies

Reference	Model	Photo	Description
<u>SAM-4535</u>	SAM-4535		Industrial power supply 12V / 60W in DIN rail format.
<u>SAM-4536</u>	SAM-4536		48V / 60W Industrial power supply in DIN rail format.
<u>SAM-4537</u>	SAM-4537		48V / 120W Industrial power supply in DIN rail format.
<u>SAM-4538</u>	SAM-4538		Industrial power supply of 48V / 240W in DIN rail format.





Storage Systems - SD Cards

Reference	Model	Photo	Description
<u>HYU-433</u>	HYU-433		16GB Micro SDHC™ memory card, Class 10 TLC, special for videosurveillance

Monitors - Desktop Monitors

Reference	Model	Photo	Description
<u>HYU-824</u>	HYU-824		

Monitors - Professional Monitors

Reference	Model	Photo	Description
<u>HYU-685</u>	HYU-685		21,5" LED monitor. 16:9. Native resolution 1080P of 1920 x 1080. 1 HDMI, 1 VGA, 1 audio input. 2 speakers of 2W. VESA 75x75.
<u>HYU-686</u>	HYU-686		24" LED monitor. 16:9. Native resolution 1080P of 1920 x 1080. 1 HDMI, 1 VGA. 2 speakers of 3W incorporated. VESA 75x75.
<u>HYU-459</u>	HYU-459		22" LED monitor. 16:9. Native resolution 1920 x 1080. 1 HDMI, 1 BNC, 1 VGA. 1x BNC output. Allows direct connection supported of CVI/TVI/AHD cameras in the HD BNC input till 5.0MP. Operation 24x7. MTBF 50.000 hours
<u>HYU-684</u>	HYU-684		28" LED monitor. 16:9. 4K of 3840 x 2160. 1 CVBS inputs, 1 Display Port, 1 HDMI, 1 DVI, 1 VGA. VESA 100x100. 24x7 working.

<u>HYU-369</u>	HYU-369		28" 4K LED monitor. 3840 x 2160 native resolution. 1 DisplayPort (4K), 2 HDMI, 1 BNC, 1 VGA, 1 audio input, USB. 1 BNC loop output. Stand is not included. Current adapter and VGA cable included
<u>HYU-536N</u>	HYU-536N		43" LED monitor. 16:9. 1920 x 1080. 5 BNC input, 1 video input, 1 HDMI, 1 VGA, 1 DVI, 1 BNC output. 24x7.
<u>HYU-535</u>	HYU-535		43" 4K LED monitor. 16:9. 3840 x 2160 native resolution. 1 HDMI, 1 DP (Display Port), 1 DVI, 1 VGA. 2x3W built in speaker. 24x7. MTBF of 50.000 hours.
<u>HYU-538</u>	HYU-538		55" 4K LED monitor. 16:9. 3840 x 2160 native resolution. 1 HDMI, 1 DP (Display Port), 1 DVI, 1 VGA. 2x3W built in speakers. 24x7. MTBF of 50.000 hours.

Monitors - Brackets / Supports

Reference	Model	Photo	Description
<u>SAM-4240</u>	SAM-4240		Ceiling mount bracket for 19" to 37" monitors. 25 kg capacity. 0°~20° inclination. 352~467 mm. VESA 200 supported.
<u>SAM-4241</u>	SAM-4241		Wall mount bracket for monitors from 23" to 55". Load capacity of 45 kg. Vertical inclination of -15 ° / + 15 °. Support up to VESA 400
<u>SAM-4243</u>	SAM-4243		Ceiling mount bracket for 23" to 55" monitors. 50 kg load. 0°~20° inclination. Extendable to 570~800 mm. VESA 400.


Video Intercoms / Video confere - IP VDP

Reference	Model	Photo	Description
-----------	-------	-------	-------------



<u>HYU-716</u>	HYU-716		HYUNDAI NEXTGEN module with blind panel for video intercom system.
<u>HYU-712</u>	HYU-712		HYUNDAI NEXTGEN indicator module for video intercom system. 8 DIP switches 1 input / output for modular connection. IP65 12V DC input / output.
<u>HYU-722</u>	HYU-722		HYUNDAI NEXTGEN framework for installing 3 built-in video door entry system modules.
<u>HYU-710</u>	HYU-710		HYUNDAI NEXTGEN display module for video intercom system. 3.5 "LCD screen (320x480). Backlit buttons. 1 input / output for modular connection. 12V DC input / output.
<u>HYU-558</u>	HYU-558		IP video doorphone station for outdoors with 1.3MP camera. 1 call button. Mifare proximity reader. Built in microphone and speaker. Fast Ethernet. Alarm: 4 in / 1 out. IP65. 12V DC. PonC.
<u>HYU-559</u>	HYU-559		IP monitor for indoors with 0,3MP camera. 7" capacitive touchscreen (1024x600). Touch keys. Panic call. Built in microphone and speaker. Fast Ethernet. Alarm: 2 in / 2 out. 12V DC. PonC.
<u>HYU-726</u>	HYU-726		HYUNDAI NEXTGEN IP video intercom kit consisting of a built-in video intercom station + 7 "touch IP monitor.

Video Intercoms / Video confere - Video Doorbells





Reference	Model	Photo	Description
<u>HYU-724</u>	HYU-724		Videotimbre IP vandal-proof HYUNDAI NEXTGEN with 1MP camera. Pinhole Optics 3.47 mm (80). Call button Access control function. It incorporates microphone and speaker. Fast Ethernet 1 inputs / 1 alarm output. 12V DC PoE

<u>HYU-561</u>	HYU-561		WiFi outdoor video doorbell. 1080P CMOS camera incorporated. Autoadaptive IR leds. 1,96 mm lens (180°). 2 way audio (microphone and speaker incorporated). MicroSD slot. Backlight call button. Reset button. IP54 (cover outdoors).
----------------	---------	---	--

Twisted Pair Transmission - Active Transmitter/Receiver

Reference	Model	Photo	Description
<u>SAM-584</u>	SAM-584		Active video receiver, audio and data over standard Cat5 UTP cable (4 twisted pair). Two male BNC connectors (two video outputs). AIRSPACE
<u>SAM-2071</u>	SAM-2071		Long-range active video receiver. Automatic gain

Twisted Pair Transmission - Pasive Transmitter/Receiver

Reference	Model	Photo	Description
<u>SAM-579</u>	SAM-579		Passive video transceiver twisted pair. male BNC connector terminal insertion cable. AIRSPACE
<u>SAM-1018</u>	SAM-1018		Passive video transceiver twisted pair with high immunity to interference
<u>SAM-581</u>	SAM-581		Passive Video Transceiver, power and data by standard UTP Cat5 cable (4 twisted pair) male BNC connector. AIRSPACE
<u>SAM-966</u>	SAM-966		16 channels passive receiver for installations with standard CAT5 RJ45 structured cable



Twisted Pair Transmission - HD Active Transmitter/Receiver

Reference	Model	Photo	Description
-----------	-------	-------	-------------


<u>SAM-4137</u>	SAM-4137		3 channel (CVI,TVI,AHD, analog) video HD active receiver. 720P and 1080P supported. Reception in real time over UTP cat5e/6. Operation with passive transmitter. It has long distance transmission, anti-interference.
-----------------	----------	---	--

Twisted Pair Transmission - HD Pasive Transmitter/Receiver







Reference	Model	Photo	Description
<u>HYU-159</u>	HYU-159		1 channel passive transciever (HDCVI, HDTVl and AHD via twisted pair). 2 units pack
<u>HYU-157</u>	HYU-157		1 channel passive transciever (HDCVI, HDTVl and AHD via twisted pair)
<u>HYU-157N</u>	HYU-157N		Pack of 2 passive transceivers of 1 video channel HDCVI, HDTVl and AHD per twisted pair
<u>SAM-2833</u>	SAM-2833		1-channel passive transceiver HD-CVI / HD-TVl / AHD / analog
<u>HYU-158</u>	HYU-158		1 channel passive transciever (HDCVI, HDTVl and AHD via twisted pair)
<u>SAM-2838N</u>	SAM-2838N		Passive transmitter of 1 video channel and power supply for HD-CVI/HD-TVl/AHD.
<u>SAM-4235</u>	SAM-4235		Passive HD video transceiver (HDCVI / HDTVl / AHD) with 4 channels 720P / 1080P / 4MP.

<u>SAM-4237</u>	SAM-4237		Passive HD video transceiver (HDCVI / HDTV / AHD) with 16 channels 720P / 1080P / 4MP.
<u>HYU-449</u>	HYU-449		8 channel HD video receiver (HDCVI/HDTV/AHD) and power supply of 8 channels of 24V

Accesorios - Recorder Accesorios



Reference	Model	Photo	Description
<u>SAM-2023N</u>	SAM-2023N		3G wireless modem. GSM, GPRS, EDGE. SIM slot.

Accesorios - Accesorios/Complementos varios


Reference	Model	Photo	Description
<u>SAM-1046</u>	SAM-1046		Twisted pair transformer filter
<u>SAM-3491</u>	SAM-3491		Smoked dome for IP domes (SAM-3033 /3040 /3044 /3488)
<u>SAM-592</u>	SAM-592		Female DB9 RS232 to 2 wire RS-485 terminal. AIR SPACE
<u>SAM-601</u>	SAM-601		Protection against electric shock in twisted pair. AIR SPACE
<u>SAM-603</u>	SAM-603		Ground loop isolator to eliminate video interference in twisted pair. Passive transceiver. AIR SPACE
<u>SAM-732</u>	SAM-732		Ground Loop Isolator for audio. Pack x2

<u>SAM-4160</u>	SAM-4160		HD-TVI/HDCVI/AHD Surge Protector
<u>SAM-1045</u>	SAM-1045		Set of two converters that supplies (12V DC) for IP cameras
<u>SAM-731</u>	SAM-731		Distribution box 1 input / 9 outputs.
<u>SAM-602</u>	SAM-602		Ground loop isolator to eliminate video interference on coaxial cable. AIR SPACE
<u>SAM-604</u>	SAM-604		High quality loop isolator to eliminate interference of video in coaxial cable
<u>SAM-605</u>	SAM-605		Loop isolator of high quality to eliminate interference of video in twisted pair cable, high-quality.
<u>SAM-734</u>	SAM-734		Power, video and data protection
<u>SAM-1052</u>	SAM-1052		USB Converter to UTP CAT5/E Cable
<u>SAM-606N</u>	SAM-606N		High frequency interference block (RF modulator), electromagnetic waves, high voltage electricity, radio stations. Video and audio via coaxial cable.
<u>SAM-748N</u>	SAM-748N		16 video channel surge protector TVI/AHD/CVI/CVBS. For rack 1U mount.




Accesorios - Amplifier / Video Extender

Reference	Model	Photo	Description
<u>SAM-597</u>	SAM-597		1 input 1 output video amplifier
<u>SAM-2887</u>	SAM-2887		HDMI to RF extender/modulator (TX+RX), 700 m


Accesorios - Professional Audio

Reference	Model	Photo	Description
<u>SAM-809</u>	SAM-809		High sensitivity ceiling microphone and noise rejection

Accesorios - Cable & Hoses








Reference	Model	Photo	Description
<u>SAM-4442</u>	SAM-4442		UTP unshielded cable of 5 meters with RJ45 connectors, 5E category
<u>SAM-4443</u>	SAM-4443		UTP unshielded cable of 10 meters with RJ45 connectors, 5E category.
<u>SAM-612</u>	SAM-612		1m length multiple cable assembly with BNC male connectors on both sides. 4 coaxial links.

Accesorios - Housing & Camera Brackets

Reference	Model	Photo	Description
<u>HYU-574</u>	DS-2102ZJ		Wall mount for counting people camera HYU-519

<u>HYU-693</u>	DS-2102ZJ-WHITE		Wall mount for people counting camera HYU-519
<u>HYU-172</u>	HYU-172		Deep base for HYU-22N, HYU-42N, HYU-43N, HYU-55, HYU-55N, HYU-58, HYU-182, HYU-171
<u>HYU-472</u>	HYU-472		Junction box for HYU-186
<u>HYU-359</u>	DS-1259ZJ		Base with 15° tilt for HYUNDAI domes
<u>HYU-212</u>	DS-1258ZJ		Wall mount for HYUNDAI domes. Inside wire passage: ABS plastic and polycarbonate. 2 Kg load
<u>HYU-153</u>	HYU-153		Deep base for HYU-98, HYU-102, HYU-103, HYU-178, HYU-188
<u>HYU-27</u>	HYU-27		TUBE BASE FOR DOME HYU-14N, HYU-15N, HYU-96, HYU-97, HYU-101, HYU-177, HYU-187
<u>SAM-1956</u>	SAM-1956		Wall Bracket for SAM-1954 / 1955 anti-vandal domes
<u>SAM-4359</u>	SAM-4359		Mount and junction box base for cameras and fixed lens dome, small size. White color

Net prices VAT not included. Offer valid until 21/06/2020 or end of stock. PROMOTION CODE: EN210520.



<u>SAM-4360</u>	SAM-4360		Mount and junction box base for cameras and fixed lens dome, small size. Ivory color
<u>SAM-3580</u>	SAM-3580		Wall mount for SAM-3575 and SAM-3576 domes
<u>SAM-541</u>	SAM-541		Bracket container with swivel for SAM-542, 543, 544, 545, 546
<u>HYU-835</u>	HYU-835		Support for HYUNDAI and AirSPACE Minidomes
<u>HYU-361</u>	DS-1250ZJ		Rain protection visor for HYUNDAI domes
<u>HYU-355</u>	HYU-355		Junction box base for HYU-333, HYU-336, HYU-337
<u>SAM-4357</u>	SAM-4357		Mount and junction box base for cameras and varifocal domes, big size. Ivory color
<u>SAM-4358</u>	SAM-4358		Mount and junction box base for cameras and varifocal domes, big size. dark grey color
<u>HYU-25</u>	HYU-25		- Wall mount for domes HYU-12, HYU-23, HYU-44, HYU-45

<u>SAM-4146</u>	SAM-4146		Universal connection box for bullets and dome cameras. Metal and Plastic. For Indoor use
<u>HYU-365</u>	DS-1281ZJ-DM23		Inclined base for HYUNDAI domes. Aluminum. 4,5 kg load.
<u>SAM-3026</u>	SAM-3026		Grey connection box with cable passage
<u>SAM-3027</u>	SAM-3027		Grey connection box with cable passage
<u>SAM-4479</u>	SAM-4479		Universal junction box for bullet or domes. Made of metal. Suitable for outdoors, IP66. Dark grey color
<u>HYU-54</u>	HYU-54		Ceiling mount HYU-49, HYU-50, HYU-51, HYU-52, HYU-81, HYU-82
<u>HYU-219N</u>	DS-1662		Ceiling bracket (long) for HYUNDAI and HiWatch™ HIKVISION® dome. Aluminum. Indoor/outdoor
<u>HYU-218</u>	DS-1661ZJ		Ceiling mount for HYUNDAI motorized domes. Aluminum. Indoor/Outdoor. 30 kg load




<u>HYU-842</u>	DS-1272ZJ-110-TRS-BLACK		Wall mount for HYUNDAI domes. Aluminium alloy. Side and bottom entrance. Capacity of 4.5 kg. Suitable interior and exterior.
<u>HYU-521</u>	DS-1281ZJ-S		Inclined base for HYUNDAI domes. Aluminum. 4,5 kg load.
<u>HYU-575</u>	DS-1227ZJ-P1		Ceiling bracket for people counting camera HYU-519
<u>HYU-545</u>	DS-1273ZJ		Junction box for HYUNDAI and HiWatch™ HIKVISION® PTZ domes
<u>HYU-219</u>	DS-1662ZJ		Ceiling mount (50 cm) for HYUNDAI motorized domes. Aluminum. Indoor/outdoor. 30 kg load
<u>HYU-598</u>	DS-1273ZJ-130		Wall mount for HYUNDAI domes. Aluminium alloy. Wiring input hole. 4,5 kg load
<u>HYU-56</u>	HYU-56		Support bracket HYU-49, HYU-50, HYU-51, HYU-52, HYU-81, HYU-82
<u>HYU-363</u>	DS-1281ZJ-M		Inclined base for HYUNDAI domes. Aluminum. Capacity of 4,5 kg.

<u>HYU-838</u>	DS-1280ZJ-S-BLACK		HYUNDAI dome base. Aluminium alloy. Side and bottom entrance. Capacity of 4.5 kg. Suitable for indoors and outdoors.
<u>HYU-841</u>	DS-1281ZJ-M-BLACK		Inclined base for HYUNDAI domes. Aluminium alloy. Side and bottom entrance. Capacity of 4.5 kg. Suitable interior and exterior.
<u>HYU-202</u>	DS-1227ZJ		Embedded ceiling mount bracket for HYUNDAI domes. Aluminum. 4.5 kg load
<u>HYU-843</u>	DS-1273ZJ-130-TRL-BLACK		Wall mount for HYUNDAI domes. Aluminium alloy. Side and bottom entrance. Capacity of 4.5 kg. Suitable for indoors and outdoors.
<u>HYU-599N</u>	DS-1271ZJ-130		Ceiling mount for HYUNDAI domes. Aluminum alloy. Wiring input hole. 4,5 kg load.
<u>HYU-360</u>	DS-1271ZJ-110		Ceiling mount for HYUNDAI domes. Waterproof. Cable passage through the interior. Aluminum. Capacity of 4,5 kg.
<u>SAM-2853</u>	SAM-2853		Corner support for CTD-462, SAM-1973N, SAM-2778, SAM-2779 and SAM-2785
<u>HYU-364</u>	DS-1271ZJ-135		Ceiling bracket (long) for HYUNDAI domes. Aluminum. 4,5 kg load

<u>HYU-208</u>	DS-1602ZJ-POLE		Column bracket for HYUNDAI domes HYU-205, HYU-222, HYU-242. Aluminum and steel. 67~127 mm. 30 kg load
<u>SAM-552</u>	SAM-552		Outdoor aluminum container. Heater and Fan. Dimensions: 390X142x115 mm. 220V AC.
<u>SAM-543</u>	SAM-543		Outdoor aluminum container. Heater. Dimensions: 390 X 142 x 115 mm. 220 V AC.
<u>SAM-3072</u>	SAM-3072		304 steel bracket (316 on request) for SAM-3067/3068/3069/3070
<u>HYU-602</u>	DS-1271ZJ-140-DM45		Ceiling bracket for HYUNDAI domes. Aluminum alloy. Wiring input hole. 4,5 kg load.
<u>HYU-210</u>	DS-1660ZJ		Parapet mount for HYUNDAI domes. Aluminum. 30 kg load
<u>HYU-546</u>	DS-1602ZJ-BOX		Junction box for HYUNDAI and HiWatch™ HIKVISION® PTZ domes
<u>SAM-3071</u>	SAM-3071		304 steel bracket (316 on request) for SAM-3067/3068/3069/3070
<u>HYU-578</u>	DS-1619ZJ		Cornice bracket for HYUNDAI PTZ domes


<u>SAM-4643</u>	SAM-4643		
<u>SAM-3067</u>	SAM-3067		Explosion proof case. 316 stainless steel. 86KPa~106KPa. IP66. ATEX certificate

Accesorios - Connectors & Accesorios





Reference	Model	Photo	Description
<u>SAM-4447</u>	SAM-4447		1 LAN port phone jack.
<u>SAM-4449</u>	SAM-4449		Rear box for wall mount
<u>HYU-351</u>	HYU-351		RCA connector (female) with insertion terminal
<u>HYU-350</u>	HYU-350		BNC connector (female) with insertion terminal
<u>SAM-3897</u>	SAM-3897		HDMI female to HDMI female connector
<u>SAM-4376N</u>	SAM-4376N		Keystone RJ45 connector module (5e category female)

<u>SAM-3898</u>	SAM-3898		DVI adapter (24+1) male to HDMI male
<u>SAM-3894</u>	SAM-3894		HDMI male to 2x HDMI female splitter
<u>SAM-3895</u>	SAM-3895		1 VGA male to 2 VGA female splitter

Accessories - Video Converters


Reference	Model	Photo	Description
<u>SAM-4513</u>	SAM-4513		Compound video signal converter CVBS (RCA) and stereo audio signal (RCA L + R) to HDMI signal. Supports PAL and NTSC input signal. Supports output signal up to 1080P. Includes miniUSB cable for power.

Accessories - Data & Video distributors

Reference	Model	Photo	Description
<u>SAM-596</u>	SAM-596		1 input 4 outputs video distributor
<u>SAM-4519</u>	SAM-4519		HDMI splitter at 8 HDMI outputs. 4K/2K at 30Hz.
<u>SAM-1050</u>	SAM-1050		Additional receiver for SAM-1049
<u>SAM-4512</u>	SAM-4512		4 channel video and HD audio multiplexor. 4 HDMI inputs at 1 HDMI output. Supports full-screen viewing of video and audio or image division modes in a single display device. Up to 1080P 60Hz. Includes power adapter and infrared remote control.




<u>SAM-767</u>	SAM-767		1 Input / 4 outputs distributor
<u>SAM-4521</u>	SAM-4521		Matrix switch of 4 HDMI input at 2 output groups (HDMI + Coaxial Audio + Audio 3.5 + SPDIF audio).
<u>SAM-4520</u>	SAM-4520		HDMI splitter at 16 HDMI outputs. 4K/2K at 30Hz.
<u>SAM-736</u>	SAM-736		Distributor (rack) 1 RS232 or RS485 input / 8 RS485 output
<u>SAM-1048</u>	SAM-1048		VGA distribution: 1 input 2 outputs
<u>SAM-746</u>	SAM-746		16 input 64 output video distributor




Accesories - Night Vision Spotlights

Reference	Model	Photo	Description
<u>SAM-4222</u>	SAM-4222		Column bracket for IR spotlight SAM-1829
<u>SAM-2390</u>	SAM-2390		1 led focus IR illumination range 28 meters, 45 °
<u>SAM-2391</u>	SAM-2391		1 led focus IR illumination range 20 meters, 60 °






<u>SAM-2392</u>	SAM-2392		1 led focus IR illumination range of 10 meters, 90 °
<u>SAM-4270</u>	SAM-4270		Column support for infrared spotlights SAM-1829, SAM-1830 and SAM-1831.
<u>HYU-475</u>	HYU-475		Spotlight with IR illumination of 6 LED. Vandal protection. 40 meters range, 45°. IP66, IK10.
<u>HYU-650N</u>	HYU-650N		IR Spotlight with vandal protection (12 led IR), high power of 100 meter range, 30°. IP66, IK10.
<u>SAM-2056</u>	SAM-2056		IR illumination light up to 210 meters, 30 °





Accesories - Power Supplies

Reference	Model	Photo	Description
<u>SAM-6688</u>	SAM-6688		Power cord for electrical devices. UK 3P plug. 2x0.75mm ² CU. 13A, 250V. BS, CE, RoHS.
<u>SAM-762</u>	SAM-762		Power supply for cameras 12V / 500 mA.
<u>HYU-479</u>	HYU-479		Power supply. 110V~220V AC input. 12V DC output, 1A. IP66.

<u>SAM-2021N</u>	SAM-2021N		
<u>SAM-610</u>	SAM-610		8 outputs, 12 V / 500mA stabilized power supply
<u>SAM-611</u>	SAM-611		16 outputs 500mA 12 V stabilized power supply. 500mA each





Accessories - Tools

Reference	Model	Photo	Description
<u>SAM-4246</u>	SAM-4246		Stripper for coaxial, with interchangeable blades compatible with RG-58/59/62 / 4C / 5C cables.
<u>SAM-4259</u>	SAM-4259		Telecommunication splicing crimping tool
<u>SAM-4264</u>	SAM-4264		Round cut wire strippers for multi-conductor cable. Cuts O.D. cable up to 10.5 mm.
<u>SAM-4267</u>	SAM-4267		Cable stripper for flat and round, compatible with cables RG-59/6/11/7
<u>SAM-4263</u>	SAM-4263		Coaxial wire stripper used to strip round cables RG174 / 58/59/62/6 3C / 4C / 5C (Ø2,6 ~ 8)

<u>SAM-4262</u>	SAM-4262		Flange tensioner from 2.4 to 9.5 mm with blade
<u>SAM-4265</u>	SAM-4265		Round cut wire strippers for multi-conductor cable. Cuts O.D. cable up to 19.1 mm
<u>SAM-4248</u>	SAM-4248		Compression coaxial cable crimper for BNC RCA RG59
<u>SAM-4261</u>	SAM-4261		7-piece coaxial network tool case. Suitable for the preparation of custom cables, compatible with almost all standard sizes. Includes adapters for different types of cables and coaxial connectors.

Accessories - Racks & Safe Boxes

Reference	Model	Photo	Description
<u>SAM-4452</u>	SAM-4452		Wiring management panel with 5 plastic rings. Metal and ABS plastic. Black color. For racks and 19" standard boxes(1U)
<u>SAM-4231</u>	SAM-4231		Cable organizer for rack. 1U.
<u>SAM-4415</u>	SAM-4415		Fan for racks SAM-4232 and SAM-4238.
<u>SAM-4279</u>	SAM-4279		1U tray for corner rack cabinet SAM-4232. 483 mm width and 230 mm depth.



<u>SAM-4277</u>	SAM-4277		1U tray with vent holes for corner rack cabinet SAM-4232. 483 mm width and 230 mm depth.
<u>SAM-4280</u>	SAM-4280		1U tray for corner rack cabinet SAM-4238. 483 mm width and 350 mm depth
<u>SAM-4278</u>	SAM-4278		1U tray with vent holes for rack corner cabinet SAM-4238. 483 mm width and 350 mm depth.
<u>SAM-4397</u>	SAM-4397		2x Fan kit for racks SAM-4233 and SAM-4239
<u>SAM-4230</u>	SAM-4230		Patch panel of 24 ports UTP/RJ45 on rack format
<u>SAM-4365</u>	SAM-4365		Vertical wall mount for safety box SAM-4363
<u>SAM-4232</u>	SAM-4232		19" rack closet -6U for corner installation. 60 kg load. IP20. SSPC. 430 mm depth.
<u>SAM-4238</u>	SAM-4238		19"-6U rack cabinet to install on corners. 60 kg load. IP20. SSPC. 600 mm depth

<u>SAM-4239</u>	SAM-4239		19"-9U rack cabinet for wall mount. 100 kg load. IP20. SPCC. 600 mm depth
---------------------------------	----------	---	---

Accesorios - KVM Solutions

Reference	Model	Photo	Description
<u>SAM-3507</u>	SAM-3507		6ft (1.83m) USB/VGA KVM cable. Connect computers with VGA and USB ports to a SAM-2921 KVM switch.

Accesorios - Testers & Multifunction Monitors

Reference	Model	Photo	Description
<u>SAM-4260</u>	SAM-4260		Network cable tester with LCD viewer.
<u>SAM-4066</u>	SAM-4066		5 in 1 multifunction CCTV tester with 4" TFT display with TVI/CVI/AHD (3.0) support up to 3MP/4MP and IP H.265 of 4K. Audio input/output. PTZ control. UTP test. TDR function. PoE output. 12V power supply output. Onvif supported. BNC input/output.

Accesorios - HDMI WiFi Transmission

Reference	Model	Photo	Description
<u>SAM-2888</u>	SAM-2888		Extensor HDMI vía radio de 200 metros




Last units

CCTV - Camaras CVI/ TVI/ 4 En 1

Reference	Model	Photo	Description
-----------	-------	-------	-------------

 <u>SAM-3431</u>	SAM-3431		4 in 1 fixed dome LITE series with IR illumination of 30 meters for outdoors. 1/3" CMOS Primesensor, 1.3MP @ 720p. 4 in 1 output (HDCVI/HDTV/ AHD/960H). 3.6 mm fixed lens. AWB, AGC, AES, 2D-NR. IP66. 3AXIS. 12V DC.
 <u>HYU-469</u>	HYU-469		4 in 1 bullet camera PRO series with IR up to 20 m for outdoors. 1/2,5" CMOS, 5 MP. 4 in 1 output (HDCVI / HDTV / AHD / 960H). ICR filter. 0,02 lux. 3,6 mm fixed lens. OSD, AWB, AGC, BLC, HLC, digital WDR, 2D/3D-DNR, defog, mirror, motion detection. IP66. 3AXIS bracket. 12V DC.
 <u>HYU-275</u>	HYU-275		4 in 1 fixed dome PRO series with IR of 20 m, for outdoors. 1/2,9" Sony® CMOS, 5 MP. 4 in 1 output by DIP switch (HDCVI @4MP / HDTV @5MP / AHD @5MP / CVBS @960H). ICR filter. 2,8 mm fixed lens. OSD, WB, AE, DNR, mirror. IP66. 3AXIS. 12V DC.
 <u>SAM-3753</u>	SAM-3753		4 in 1 fixed dome LITE series with IR illumination of 40 m, for outdoors. 1/3" CMOS, 1,3MP @ 960P. 4 in 1 output DIP switch (HDCVI / HDTV / AHD / 960H). 2,8~12 mm varifocal lens. ICR filter. No OSD. IP66. 3AXIS. 12V DC.
 <u>SAM-4006</u>	SAM-4006		4 in 1 bullet camera PRO series with IR illumination of 25 m, for outdoors. 1/2,9" Sony Exmor CMOS, 5 and 4 MP. 4 in 1 output (HDCVI / HDTV / AHD / 960H). ICR filter. 2,8mm fixed lens. OSD, AWB, AGC, 2D-NR, HLC. IP66. 3AXIS. 12V DC
 <u>SAM-3573</u>	SAM-3573		IP bullet camera with IR illumination of 20 m, for outdoors. H.264/MJPEG. 1/2,9" Sony® CMOS, 2 MP. 1080P @25/30 fps. 2,8 mm fixed lens. ICR. OSD, WDR digital, 2 way audio. Onvif. IP66. Waterproof cable. Reset button. 12V DC. PoE.
 <u>SAM-4011</u>	SAM-4011		4 in 1 dome PRO series with IR illumination of 30 m, for indoors. 1/2,9" Sony Exmor CMOS, 5 and 4 MP. 4 in 1 output (HDCVI / HDTV / AHD / 960H). ICR. 2,7-13,5mm manual varifocal lens starlight. OSD, AWB, AGC, 2D-NR, HLC. 3AXIS. 12V. Plastic construction
 <u>SAM-4353N</u>	SAM-4353N		4 in 1 bullet camera PRO series with Smart IR of 40 m for outdoors. 1/2,7" CMOS, 5MP. 4 in 1 output (HDCVI / HDTV / AHD / 960H). ICR filter. 2,7 ~ 13,5 mm varifocal lens. OSD, AWB, MWB, AGC, BLC, digital WDR, 2D-NR. IP66. 12V DC.

NEW

<u>SAM-3576</u>	SAM-3576		Fixed IP dome with IR illumination of 30 meters, vandal protection, for outdoors. H.265/MJPEG. 1/3" CMOS, 4 MP. 4MP @15 fps. 2,8 ~ 12 mm autofocus motorized lens. ICR. OSD, WDR, 3D-DNR, 2 way audio, motion detection and privacy mask. Pipe thread base. Onvif. IP66. Waterproof cable. Reset button. 12V DC. PoE.
<u>HYU-241</u>	HYU-241		IP fixed vandal dome with IR illumination of 30 meters, for outdoors, 2MP. H.264/MJPEG. 1/3" CMOS, 2MP. 1080p/1.2MP/720p. Mechanical filter. 0.014 lux. 2.8~12 mm varifocal lens (113°~33.8°). OSD, 3D-NR, BLC, digital WDR, privacy mask, ROI, Intelligent functions (IVS). MicroSD/SDHC/SDXC. IP67, IK10. 3AXIS. 12V DC. PoE
<u>SAM-3333</u>	SAM-3333		HDCVI fixed dome PRO series with IR illumination of 50 m, for outdoors. 1/2.8" CMOS, 2.1MP @ 1080p. Dual output (HDCVI/960H). 2.7~12 mm motorized lens (autofocus), 95°~36° Starlight 3rd generation. 0.005 lux. ICR. OSD, AWB, AGC, BLC, 2D/3D-NR, WDR real (120 dB). Audio input. Alarm: 1 in / 1 out. Heater. IP67. IK10. 24V AC / 12V DC
<u>HYU-286</u>	HYU-286		IP vandal dome with IR illumination of 30m, for outdoors, 8 MP. H.265/H.264/MJPEG. 1/2,5" CMOS, 8MP. Triple stream. Mechanical filter. 0,01 lux. 2,8 mm fixed lens (102°). OSD, 3D-NR, BLC, real WDR 120dB, privacy mask, 1 ROI zone. IVS. MicroSD//SDHC/SDXC slot. IP67, IK10. 3AXIS. 12V DC. PoE.

CCTV - DVR / XVR

Reference	Model	Photo	Description
<u>SAM-3470</u>	NB-XVR4116HS		16 channel 5 in 1 XVR (HDCVI/HDTVII/AHD/CVBS + 2 IP at 5MP). H264. Audio (4 in / 1 out). 16 ch @ 1080N. Recording: 1080N, 720P, 960H, D1/4CIF, VGA, CIF, QVGA, QCIF, full 1080N/720P in all cameras. HDMI and VGA output @ 1080P with SPOT function. Intelligent Video Surveillance. Facial detection. 1 HDD SATA. Onvif, CGI. 2 USB. 12V DC. SMARTPSS, IDMSS y P2P.
<u>SAM-3522</u>	NB-HCVR7104H-4M		4 channel HDCVI trihybrid DVR (960H and/or HDCVI 2K/4MP+ 2 IP channels @ 5MP). H.264+. Audio (1in/1out). Simultaneous playback. Recording at 2K/4MP, 1080p, 720p, etc. Full 1080p @ 30 fps. HDMI &VGA output. SPOT output.. 1 HDD SATA. 1RJ45 Gigabit, 1 USB 3.0 + 1 USB 2.0. 12VDC. Mini 1U. Compatible with official SMARTPSS, IDMSS and P2P.

CCTV - IP Hyundai


Reference	Model	Photo	Description
<u>HYU-206</u>	NVR4104-6M		4 channel IP NVR. H.264+. 4 ch @ 1080p synchronous display. 6MP display. Recording: 6MP, 5MP, 4MP, 3MP, 1080P, 720P, D1/4CIF, etc. 40 Mbps. VGA and HDMI output @ 1080p. Two-way audio. 1HDD SATA. Onvif, P2P, DDNS, 12V DC. 1U.

NEW








NEW

NEW

NEW

<u>HYU-313</u>	HYU-313		Fixed IP dome with IR illumination of 20~30m, for outdoors, 4 MP. H.264/H.264+/MJPEG. 1/3" CMOS, 4MP. Digital resolution: 4MP, 3MP, 1080P, 720P, etc. Mechanical filter. 0,01 lux. 2,8~12 mm motorized lens (98°~30°) with autofocus. OSD, AGC, BLC, real WDR 120dB, 3D-DNR, motion detection, privacy mask, fixed ROI zones. IP67. 3AXIS. 12V DC. PoE.
----------------	---------	---	---

CCTV - Accesorios

Reference	Model	Photo	Description
<u>SAM-2544</u>	SAM-2544		Black Base with tube passage
<u>SAM-2547</u>	SAM-2547		Black Base with tube passage
<u>SAM-2855</u>	SAM-2855		Inner roof support for SAM-1973N
<u>SAM-2050N</u>	SAM-2050N		Suspended ceiling support (23cm) for motorized domes sam-1972, sam-1973
<u>HYU-59</u>	HYU-59		Corner bracket for HYU-49, HYU-50, HYU-51, HYU-52, HYU-81, HYU-82
<u>SAM-2538</u>	SAM-2538		1 channel IP receiver over UTP, up to 500 m
<u>SAM-2471</u>	SAM-2471		Portable audio/video tester. Designed for wrist fixing. 3,5" LCD. 1 RCA in of video/audio.

NEW

NEW




NEW

Access Ctrl

Access Ctrl/Presence - Controllers

Reference	Model	Photo	Description
<u>HYU-638</u>	HYU-638		Access control controller. 2 door access control. Up to 10.000 cards and 50.000 events. Uplink by TCP/IP communication. 4 Wiegand readers. 2 door sensor input, 2 REX exit button and 2 alarm input. 2 Relay output for door lock and 2 alarm relay.
<u>HY</u>	HYU-727		Access Control Controller. Access control of two doors. Up to 100,000 cards and 300,000 events. Uplink communication via RS485 and TCP / IP. 4 Wiegand readers, 4 RS485 readers. Inputs for 2 door sensors, 2 REX output buttons, 4 alarm inputs and 1 tamper input. Outputs for 2 door lock relays and 4 alarm relays.

Access Ctrl/Presence - Autonomous Reader




Reference	Model	Photo	Description
<u>HYU-729</u>	HYU-729		Standalone HYUNDAI Access Control and Presence terminal with biometric fingerprint reading and EM card reader. Up to 1,000 fingerprints, 1,000 cards, 1,000 users, 100,000 events and 50,000 attendance records. It incorporates a 2.4" screen. TCP / IP communication. Inputs for 1 door sensor and 1 REX output button. Outputs for 1 door lock relay and 1 doorbell relay. Not suitable for outdoor use.
<u>HYU-728</u>	HYU-728		Standalone HYUNDAI Access Control terminal with biometric fingerprint reading and MIFARE card reader. Up to 3,000 fingerprints, 3,000 cards, 100,000 events and 150,000 attendance records. It incorporates 2.4 "screen. TCP / IP and RS485 communication. Inputs for 1 door sensor and 1 REX output button. Outputs for 1 door lock relays. Not suitable for outdoor use.
<u>HYU-639</u>	HYU-639		Standalone access control terminal with facial recognition, biometric fingerprint reader and Mifare card reader. Up to 3.000 facial images, 5.000 fingerprint, 5.000 cards and 100.000 events. 5" touchscreen and 2 MP wide lens camera with WDR. TCP/IP and WiFi. 1 door lock input, 1 REX exit button, 1 tamper and 1 alarm input. 1 Relay output for door lock and 1 alarm relay. Centralised power supply

Access Ctrl/Presence - Readers

Reference	Model	Photo	Description
<u>HYU-642</u>	HYU-642		EM 125 KHz card reader. 50 mm reading range. Wiegand 26/34 communication. For outdoors.

<u>HYU-643</u>	HYU-643		Mifare 13,56 MHz card reader, vandal protection IK10. 50 mm reading range. Wiegand 26/34 communication. RS485. Suitable for outdoors.
<u>HYU-644</u>	HYU-644		Mifare 13,56 MHz card reader, IK10 vandal protection. 50 mm reading range. Keyboard incorporated. Wiegand 26/34 communication. RS485. Suitable for outdoors.
<u>HYU-645</u>	HYU-645		Fingerprint and Mifare card reader. Up to 5.000 fingerprints. Card reading range 3 to 10 cm. RS485 communication. Suitable for outdoors.

Access Ctrl/Presence - Access / Attendance Terminal

Reference	Model	Photo	Description
<u>HYU-731</u>	HYU-731		Standalone HYUNDAI Presence Control terminal with biometric fingerprint reading and EM card reader. Up to 1,000 fingerprints, 1,000 cards, 1,000 users, 100,000 events and 50,000 attendance records. It incorporates 2.4 "screen. TCP / IP communication. Not suitable for outdoor use.
<u>HYU-732</u>	HYU-732		Standalone HYUNDAI Presence Control terminal with biometric fingerprint reading and MIFARE card reader. Up to 1,000 fingerprints, 1,000 cards, 1,000 users, 100,000 events and 50,000 attendance records. It incorporates 2.4" screen. TCP / IP communication. Not suitable for outdoor use.
<u>HYU-730</u>	HYU-730		Standalone HYUNDAI Access Control and Presence terminal with biometric fingerprint reading and MIFARE card reader. Up to 1,000 fingerprints, 1,000 cards, 1,000 users, 100,000 events and 50,000 attendance records. It incorporates a 2.4 "screen. TCP / IP communication. Inputs for 1 door sensor and 1 REX output button. Outputs for 1 door lock relay and 1 doorbell relay. Not suitable for outdoor use.

Accessories - Reader / Desktop Programmer








Reference	Model	Photo	Description
<u>HYU-646</u>	HYU-646		EM and Mifare® USB card registrator. Plug&Play (without controllers). Power supply led indicator and status communication. USB power supply.

<u>HYU-647</u>	HYU-647		USB fingerprint register. Plug&Play connection (without controllers). USB power supply.
----------------	---------	---	---

INTRUSION

DYI Home system alarm GRADE 1 - Hyundai Smart4Home Alarm

Reference	Model	Photo	Description
<u>HYU-68</u>	HYU-68		Remote push button via radio for Smart4Home system
<u>HYU-67</u>	HYU-67		Magnetic contact via radio for Smart4Home systems
<u>HYU-66</u>	HYU-66		PIR sensor via radio for Smart4Home systems
<u>HYU-75</u>	HYU-75		Intelligent socket for Smart4Home systems
<u>HYU-141</u>	HYU-141		LED bulb via radio for Smart4Home systems
<u>HYU-71</u>	HYU-71		Keyboard via radio

<u>HYU-77</u>	HYU-77		Intelligent socket with intensity regulator
<u>HYU-73</u>	HYU-73		FLOOD SENSOR VIA RADIO
<u>HYU-76</u>	HYU-76		Intelligent socket with consumption calculation
<u>HYU-69</u>	HYU-69		Indoor voice siren for Smart4Home system
<u>HYU-70</u>	HYU-70		Outdoor solar siren via radio
<u>HYU-74</u>	HYU-74		WiFi IP compact camera for Smart4Home systems, with IR illumination and PIR sensos. H.264. 1MP@30 fps. Microphone and speaker. MicroSD slot. Onvif. 220V AC (power supply included).
<u>HYU-65</u>	HYU-65		Smart4Home kit composed by: IP station control (sold separately), 720p IP camera HYU-74, indoor voice siren HYU-69, PIR detector HYU-66, magnetic contact HYU-67, remote push HYU-68, Hyundai Smart4Home software